Multi-Vehicle ATF 2

Proven performance automatic transmission fluid

Product description

Multi-Vehicle ATF 2 is a proven performance automatic transmission fluid formulated for use in passenger car, light truck and bus transmissions requiring a GM DEXRON®-IID fluid.

It is formulated with premium Group II base oils and a balanced combination of additives, designed to provide efficient performance.

Customer benefits

- Specially tuned, durable friction characteristics promote smooth shifting performance throughout fluid service life.
- Low-temperature fluidity aids transmission protection during cold start-up.
- Formulated to provide oxidation stability and help prevent formation of harmful sludge, lacquer or deposits.
- Shear stability and high viscosity index help retain viscosity across operating temperature range and fluid lifetime.

Product highlights

- **Promotes smooth shifting performance**
- **Designed to provide cold start-up protection**
- **Helps prevent sludge, lacquer and deposits**
- **Formulated to retain viscosity across temperature range and fluid lifetime**

Selected specification standards include:

Daimler Truck	Ford
GM	Mercedes-Benz

Applications

- Multi-Vehicle ATF 2 is designed for use in the automatic transmissions of cars, light trucks and buses that require a GM DEXRON®-IID type fluid. Although this specification has been made technically obsolete by GM itself, many equipment manufacturers continue to recommend fluids of this type. The product is not recommended for transmissions that require a GM DEXRON®-III or DEXRON®-IV fluid.

- Multi-Vehicle ATF 2 may be used in Ford passenger car transmissions that require a Ford M2C138-CJ or M2C166-H fluid. The product is not recommended for transmissions that require a Ford MERCON® fluid. Due to fundamental differences in frictional properties, it should not be used in applications that require a Ford M2C33-F/G fluid.

- Multi-Vehicle ATF 2 is also suitable for use in power steering systems that require a mineral-type Power Steering Fluid. It should not be used in steering or active suspension systems that call for specific semi-synthetic or synthetic fluids, as the response speed may not be sufficiently fast.

- Multi-Vehicle ATF 2 may also be used as a wide temperature range anti-wear hydraulic fluid for mobile, industrial and marine applications. The viscosity is intermediate between ISO VG 32 and ISO VG 46.

Approvals, performance and suitable for use

Suitable for use

• GM	DEXRON-IID [1]
• Daimler Truck	DTFR 13C120 H
• Mercedes-Benz	MB 236.2
• Ford	ESP-M2C138-CJ
• Ford	ESP-M2C166-H
• GM	Type A Suffix A

[1] Obsolete specification

Typical test data

Test	Test Methods	Results
Typical Shelf Life: 60 months from date of filling indicated on the product label.		
Kinematic viscosity at 100°C, mm^2/s	ASTM D445	7.0
Brookfield Viscosity, -40°C, mPa.s	ASTM D2983	<50000
Colour		Red
Density, 15°C, kg/l	ASTM D1298	0.859
Flash Point, COC, °C	ASTM D92	231
Pour Point, °C	ASTM D97	-48

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see http://europe.chevronlubricants.com.

A **Chevron** company product

© 2026 Chevron. All rights reserved.
All trademarks are property owned by Chevron Intellectual Property LLC.