

Veritas[®] 800 Marine 30



Description

Veritas[®] 800 Marine 30 is a crankcase lubricant for two-stroke marine engines. Veritas 800 Marine is blended with highly refined base oils and carefully selected additives to provide very good anti-corrosion and anti-foam properties. The combination of detergency and the exceptional oxidation stability provides clean piston interiors and crankcase. Veritas 800 Marine 30 is formulated with the appropriate level of alkalinity to neutralize acidic combustion products that can enter the crankcase.

Typical Characteristics

NLGI Grade	30	
MPID	219100	
Base number, mg KOH/g (ASTM D2896)	5.6	
Density at 15°C, kg/l (ASTM D4052)	0.89	
Flash point, COC, °C (ASTM D92)	220 min	
Pour point, °C (ASTM D97)	-18	
Kinematic Viscosity at 40°C, mm²/s (ASTM D445)	100	
Kinematic Viscosity at 100°C, mm²/s (ASTM D445)	11.2	
Viscosity Index	98	
FZG test (A/8.3/90), failure load stage (CEC-L-07-95)	11	

Recommended Applications

Veritas 800 Marine 30 is recommended for the crankcase lubrication of large low-speed marine diesel engines operating with all fuel types and under all loads and operating conditions. Veritas 800 Marine 30 should be used in accordance with OEM guidelines and recommendations.

Veritas 800 Marine 30 is Approved for:

- **V** Everlience (formerly MAN ES)
- WinGD (formerly Wärtsilä)
- ✓ Japan Engine Coporation (Mitsubishi)
- ✓ Leading Stern Tube OEMs



Performance Benefits

1. Engine Protection

Helps to protect bearings and white metals in the engine lubrication systems against corrosive wear from acidic combustion by-products.

2. Engine Cleanliness

Helps maintain clean crankcases, piston interiors and lubricating oil lines.

3. Smooth Operation

Can prevent the formation of foam and ensures smooth operation of pumps with a continuous oil feed to all engine parts.

4. Easy Purification

Effective water shedding and removal of contaminants.

Environment, Health and Safety

Information is available on this product in the Safety Data Sheet (SDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain an SDS for this product visit chevronmarineproducts.com.



Disclaimer. Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Recommendations differ between engine manufacturersso always consult your manual. Neither Chevron nor its subsidiaries make any warranty or representation as to the accuracy or completeness of this PDS and neither Chevron nor its subsidiaries or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

© 2025 Chevron. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC or their respective owners.