

Havoline® Formula SAE 15W-50

Passenger Car Motor Oil



Product description

Havoline® Formula SAE 15W-50 is a highly shear stable, multigrade gasoline engine oil, designed to provide robust engine protection in passenger car and light truck engines requiring API SL performance level or lower. It is formulated with selected base fluids with an advanced additive package to help protect against starting friction, heat stress and engine deposits.

Customer benefits

- **Long engine life**
Reliable metallo-organic anti-wear additive system helps protect engines under a wide range of operating conditions, providing excellent wear control. Multigrade viscosity offers additional protection against wear, both during cold start-up and under high temperature operating conditions.
- **Helps maintain power and performance**
Advanced metallic detergent and ashless dispersant additive system helps maintain high power and performance by providing robust piston and ring deposit control, even under high temperature conditions.
- **Helps reduce maintenance costs**
High thermal stability and oxidation resistance helps provide good protection against in-service oil degradation that contributes to filter blocking and sludge formation in the oil galleries, crankcase and valve train.
- **Low oil consumption**
Highly shear stable viscosity index improver helps control oil flow through the piston rings by maintaining high-temperature oil viscosity within the ring belt area in a wide range of services.

Havoline[®] Formula SAE 15W-50

Passenger Car Motor Oil



Applications

- Naturally aspirated and turbocharged gasoline engines in passenger cars.
- Light truck gasoline engines.
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

Product approvals, performance and recommendations

Developed independently by Chevron to comply with the following performance standards and specifications:

HAVOLINE [®] FORMULA	15W-50
API SL	Approved

Consult OEM representatives for independent verification, updates and recommendations.

Havoline[®] Formula SAE 15W-50

Passenger Car Motor Oil



Typical test data

HAVOLINE [®] FORMULA SAE 15W-50	TEST METHOD	RESULTS
Base Number, mg KOH/g	ASTM D2896	5.6
Viscosity, Kinematic mm ² /s @ 40°C mm ² /s @ 100°C	ASTM D445 ASTM D445	145 18
Viscosity Index	ASTM D2270	142
Phosphorous, mass %	ASTM D4951	0.09
Sulfur, mass %	ASTM D4951	0.2
Zinc, mass %	ASTM D4951	0.10

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Havoline Formula SAE 15W-50/MEA/CHV/PDSv1_21/10/24



Chevron company product

© 2024 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.