



Clarity Bio EliteSyn ES 46

Premium performance, palm oil free, biodegradable hydraulic oil

Product description

Clarity Bio EliteSyn ES 46 a premium performance zinc-free hydraulic fluid, specially designed for use in environmentally sensitive applications.

Clarity Bio EliteSyn ES 46 is formulated with a palm oil free, fully biodegradable unsaturated ester, combined with environmentally friendly additives providing excellent oxidation stability, corrosion protection, extreme pressure (EP) and low-temp performance.

Palm oil-free hydraulic oils comply with the EU Deforestation Regulation (EUDR), ensuring that they are sourced from deforestation-free supply chains and meet stringent environmental standards.

Customer benefits

- Palm oil free formulation designed for environmentally sensitive applications where contamination may occur.
- Advanced environmentally focused additive package offers good oxidation stability, and corrosion protection.
- Engineered to provide robust protection in extreme pressure (EP) and wide operating temperature range applications (-30°C up to 90°C).
- Meets a range of environmentally focused standards including OECD 301B: >60, Swedish Standard SS 15 54 34, and WGK 1 rating according to the German WGK Classification.

Product highlights

- **Palm oil free formulation designed for sensitive environments**
- **Eco-friendly additives offer oxidation stability, corrosion protection**
- **Engineered for robust protection in extreme pressures and temperatures**
- **Meets OECD 301B, Swedish SS 15 54 34, WGK 1**

Selected specification standards include:

DIN	Eco-label
ISO	Swedish-Standard
VDMA	VGP/VIDA

Applications

Clarity Bio EliteSyn ES 46 is suited for all stationary and mobile hydraulic systems as recommended by ISO 15380, HEES.

Product should be used where there is a danger to soil or water pollution.

Typical applications are Mobile hydraulics in drainage areas and road construction, forestry and timber industry, vehicles for ski racing track maintenance, municipal vehicles and facilities, auto hoist, hydraulic engineering, forklift, horticulture and landscaping, sewage plant, freshwater recovery, floater dredgers, sluices, water maintenance boats, tunnelling machines, offshore equipment, concrete pumps, track laying machines, etc.

Seal compatibility:

In accordance with ISO 15380, it is recommended to test a variety of seals, including AU, NBR1, HNBR/1, and FKM2. These materials serve as reference standards and may differ from commercially available seal materials. It is essential to consider the applicability of the elastomer's behavior in practical use. In cases of uncertainty, compatibility testing is advised. Test conditions should be tailored to the specific application.

Approvals, performance and suitable for use

Approvals

- Swedish-Standard-15 54 34 (Environmental properties of hydraulic oils according to SS 15 54 34 | RISE)
- Certified with the EU Ecolabel for environmental excellence; EU Ecolabel: DE/027/336



Performance

- ISO 15 380 HEES
- DIN ISO 15 380 HEES
- VDMA 24568, HEES
- SS 15 54 34
- VGP/VIDA compliant

Product maintenance and handling

Always take an oil sample to evaluate the condition of the system.

When changing over to Clarity Bio Elitesyn ES 46, the guidelines for changing fluids from mineral-based oils to environmentally acceptable fluids according to DIN ISO 15 380 (HEES) has to be followed.

Check with OEMS for specific change over procedures.

Avoid any spillage of used and unused product to the environment.

Product residue and package/container should be disposed of in dedicated collection points.

Typical test data		
Test	Test Methods	Results
Typical Shelf Life: 24 months from date of filling indicated on the product label		
Appearance	Visual	Clear and bright
Colour	ISO 2049	1.5
Content of carbon of biological origin, min, %	ASTM D6866	25
Kinematic Viscosity at -20°C, mm ² /s	ISO 3104	1250
Kinematic Viscosity at 0°C, mm ² /s	ISO 3104	270
Kinematic Viscosity at 40°C, mm ² /s	ISO 3104	48.42
Kinematic Viscosity at 100°C, mm ² /s	ISO 3104	9.661
VI	ISO 2909	189
Low temperature Fluidity after 7 days, °C	ASTM D2532	-24
Density at 15°C, kg/l	ISO 12185	0.9159
Pour Point, °C	ISO 3016	-48
Flash Point, °C	ISO 2592	>300
Fire Point, °C	ISO 2592	>300
TAN, mg KOH/g	DIN ISO 6618	0.58
Foam Seq (I, II, III), ml	ISO 6247	0/0
Air release @ 50°C, min	ISO 9120	1.7
Water separation, time to 3ml emulsion at 54°C, min	ISO 6614	55min/37 ml H ₂ O
Water content, ppm	KF	299
Rust prevention, 24h, proc A & B	ISO 7120	Pass
Copper Corrosion 100°C, 3hr, rating	ISO 2160	1B

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see <http://europe.chevronlubricants.com>.

A Chevron company product