

# Havoline<sup>®</sup> EZY Plus 4T

High Quality Four-Stroke Motorcycle Oil



## Product description

**Havoline<sup>®</sup> Ezy Plus 4T SAE 20W-50** is a high-quality four-stroke motorcycle engine oil that helps offer continuous protection of the engine, gear box, and clutch under various severe city riding conditions.

## Customer benefits and product features

### Customer benefits

- **Reliable performance and protection**  
Effectively lubricates and delivers consistent performance and protection for motorcycles

### Product features

- Suitable for air- and liquid-cooled four-stroke motorcycle engines.
- Provides excellent protection and wear resistance.
- Compatible with motorcycles equipped with back torque limiters.
- Suitable for motorcycles with exhaust catalytic converters.
- Suitable for motorcycles with combined engine and transmission units or separate gearboxes where a multi-grade JASO MA or JASO MA2 engine oil is specified.

## Approvals, performance and recommendations

Developed independently by Chevron to comply with the following performance standards:

<b>HAVOLINE EZY PLUS 4T</b>	<b>SAE 20W-50</b>
JASO MA2	Meets Requirements
API SL	Meets Requirements

## Applications

The JASO MA2 category contains the highest friction motorcycle oils suitable for use in many critical oil-immersed clutch installations. Oils which meet JASO MA2 also meet the requirements of JASO MA, so may be used wherever JASO MA is specified. JASO allows an oil to be labelled as either JASO MA2 or JASO MA, but not both simultaneously.

Always refer to the owners manual of your vehicle to determine the recommended viscosity grades for the engine.

# Havoline® EZY Plus 4T

High Quality Four-Stroke Motorcycle Oil



## Typical test data

HAVOLINE EZY PLUS 4T	TEST METHOD	RESULT
<b>SAE Grade</b>		<b>20W-50</b>
<b>Product Code</b>		<b>500697</b>
Base No., mg KOH/g	ASTM D2896	6.0
Sulfated Ash, mass %	ASTM D874	0.9
Kin. Viscosity		
mm <sup>2</sup> /s @ 40°C	ASTM D445	159
mm <sup>2</sup> /s @ 100°C	ASTM D445	17.0
Phosphorus, mass %	ASTM D4951	0.09

0125

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Havoline EZY Plus 4T SAE 20W-50/MEA/CHV/PDSv2\_160125



**Chevron company product**

© 2025 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.