

Delo[®] 400 SAE 40

Heavy Duty Diesel Engine Oil



Product description

Delo[®] 400 SAE 40 is a monograde oil designed for mixed-fleets and is specifically recommended by Chevron for older four-stroke gasoline and diesel engines.

Customer benefits and product features

Customer benefits

- Helps to prevent deposit formation at piston crown and exhibits good oxidation stability to minimize oil consumption.
- Formulated to maintain engine life, good wear protection, and control deposit formulation to help protect the engine and keep it running smoothly.
- Designed to maintain engine cleanliness with detergency additives that provide excellent deposit and sludge control in the piston ring belt area.

Product features

- Delo 400 monograde heavy duty motor oils are premium quality engine oils, formulated with an advanced additive technology which helps protect four-stroke diesel engines requiring a monograde engine oil. Delo 400 SAE 40 is manufactured using premium base oils and an optimal blend of additives.

Delo[®] 400 SAE 40

Heavy Duty Diesel Engine Oil



Applications

Delo 400 SAE 40 is a mixed-fleet engine oil recommended by Chevron for older four-stroke gasoline and diesel engines that require a monograde engine oil. Delo 400 SAE 40 is formulated for exceptional performance in older engines using both normal, high, and low sulfur diesel fuels. Delo 400 SAE 40 is not recommended for use in two-stroke engines.

Product approvals, performance and recommendations

Developed independently by Chevron to comply with the following performance standards and specifications:

Delo [®] 400	SAE 40
MAN Energy Solutions: 28/33D Lubricant	Approved
MTU Category 2	Approved
API CF	Meets Requirements
MAN M3275-2	Meets Requirements
MB-Approval 228.2	Meets Requirements

Consult OEM representatives for independent verification, updates and recommendations.

Delo[®] 400 SAE 40

Heavy Duty Diesel Engine Oil



Typical test data

DELO [®] 400	TEST METHOD	RESULTS
SAE Grade		40
Product Code		500495
Base Number, mg KOH/g	ASTM D2896	10.1
Density, kg/L	ASTM D4052	0.886
Sulfated Ash, mass %	ASTM D874	1.450
Sulfur, mass %	X-ray/ICP	0.351
Viscosity, Kinematic		
mm ² /s @ 40°C	ASTM D445	136
mm ² /s @ 100°C	ASTM D445	14.7
Viscosity Index	ASTM D2270	108

0125

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Delo[®] 400 SAE 40/MEA/CHV/PDSv1_090125



Chevron company product

© 2025 Chevron Lubricants: Africa, Middle East and Pakistan. All Rights Reserved.