

Veritas[®] 800A Marine 30



Description

Veritas[®] 800A Marine 30 is a crankcase lubricant for two-stroke marine engines. Veritas 800A Marine 30 is blended with highly refined base oils and carefully selected additives to provide very good anti-corrosion and anti-foam properties. The combination of detergency and the effective oxidation stability helps provide clean piston interiors and crankcase. Veritas 800A Marine 30 is formulated with the appropriate level of alkalinity to help neutralize acidic combustion products that can enter the crankcase.

Typical Characteristics

SAE Viscosity Grade	30
MPID	219102
Base number, mg KOH/g (ASTM D2896)	5.4
Density at 15°C, kg/l (ASTM D4052)	0.88
Flash point, COC, °C (ASTM D92)	220 min
Pour point, °C (ASTM D97)	-18
Kinematic Viscosity at 40°C, mm ² /s (ASTM D445)	100
Kinematic Viscosity at 100°C, mm ² /s (ASTM D445)	11.5
Viscosity Index (ASTM D2270)	102
FZG test (A/8.3/90), failure load stage (CEC-L-07-95)	11

Recommended Applications

Veritas 800A Marine 30 is recommended for the crankcase lubrication of large low-speed marine (diesel) engines operating with all fuel types and under all loads and operating conditions. Veritas 800A Marine 30 is also used in oil lubricated stern tubes.

Veritas 800A Marine 30 should be used in accordance with OEM guidelines and recommendations.

Veritas 800A Marine 30 is Approved for:

- ☒ Everllence (formerly MAN ES)
- ☒ WinGD (formerly Wärtsilä)
- ☒ J-ENG (Japan Engine Corporation)
- ☒ Leading Stern Tube OEMs



Performance Benefits

1. Engine Protection

Helps to protect bearings and white metals in the engine lubrication systems against corrosive wear from acidic combustion by-products.

2. Engine Cleanliness

Helps maintain clean crankcases, piston interiors and lubricating oil lines.

3. Smooth Operation

Can prevent the formation of foam and helps to ensure smooth operation of pumps with a continuous oil feed to all engine parts.

4. Easy Purification

Effective water shedding and easy purification of contaminants in the lubricant.

Environment, Health and Safety

Information is available on this product in the Safety Data Sheet (SDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain an SDS for this product visit chevronmarineproducts.com.



Disclaimer: Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Recommendations differ between engine manufacturers so always consult your manual. Neither Chevron nor its subsidiaries make any warranty or representation as to the accuracy or completeness of this PDS and neither Chevron nor its subsidiaries accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.