



DELO[®] 100 MOTOR OIL ISOCLEAN[®] CERTIFIED LUBRICANT SAE 40

PRODUCT DESCRIPTION

Delo[®] 100 ISOCLEAN[®] Certified Lubricant is recommended for use in two- and four-stroke diesel engines in farm machinery, construction equipment, marine, and other off-highway applications where the SAE 40 grade is specified by the OEM.



Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.

CUSTOMER BENEFITS

Delo 100 ISOCLEAN Certified Lubricant is recommended for use in older two- and four-stroke diesel engines where the SAE 40 engine oil is specified by the OEM.

Delo 100 ISOCLEAN Certified Lubricant delivers value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.

- **High temperature deposit control** — Protects against high temperature oxidation and oil thickening in older engines.
- **Special extreme pressure antiwear properties** — Protects critical valve train components.
- **Protection against rust, corrosion, varnish, and sludge** — Helps keep oil screens, filters, and rings clean and free for prolonged periods.
- **Warranty Plus protection** — Bumper-to-bumper warranty protection from the engine to the drive train. Payment for Chevron lubricant-related damage to your equipment, including parts and labor.* Problem resolution and technical advice from Chevron's lubrication experts.
- **Access to Chevron's lubrication and industry knowledge** — Helps maximize your bottom line business results.

FEATURES

Delo 100 ISOCLEAN Certified Lubricant is a high performance crankcase oil for older diesel engines requiring an SAE 40 monograde engine oil.

It is manufactured using selected premium paraffinic base oils and detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives.

* See Warranty Plus for details and restrictions.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 June 2025
HDMO-10 ISOCLEAN

© 2025 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo and ISOCLEAN are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS

Delo® 100 ISOCLEAN® Certified Lubricant is recommended for use in two- and four-stroke diesel engines in farm machinery, construction equipment, marine, and other off-highway applications where SAE 40 grade is specified by the OEM. Delo 100 ISOCLEAN Certified Lubricant is recommended for use in two-stroke diesel engines requiring highly effective control of wear and deposits.

Delo 100 ISOCLEAN Certified Lubricant utilizes exceptional quality technology to provide excellent performance in older engines burning ultra low sulfur diesel fuels.

Delo 100 ISOCLEAN Certified Lubricant meets the requirements of:

- **API Service Categories**
 - CF[†], CF-2[†]
- **Detroit Diesel Corporation two-stroke** engine recommendations, including the 0.85% ash maximum limit for Series 149 engines.

TYPICAL TEST DATA

SAE Grade	40
<i>Product Number</i>	<i>257016</i>
<i>SDS Number</i> <i>U.S.</i> <i>Canada</i>	<i>7329</i> <i>7329CAN</i>
API Gravity	27.7
Viscosity, Kinematic cSt at 40°C cSt at 100°C	145 15.0
Viscosity Index	104
Flash Point, °C(°F)	258(498)
Pour Point, °C(°F)	-24(-11)
Sulfated Ash, wt %	0.80
Base Number, ASTM D2896	7.3
Phosphorus, wt %	0.096
Zinc, wt %	0.105

Minor variations in product typical test data are to be expected in normal manufacturing.

[†] Obsolete specification.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.