

### Product description

**Capella® HFC** refrigeration oils are high performance fully synthetic fluids designed for the lubrication of compressors used in refrigeration and air conditioning systems and are blended exclusively with specially selected polyol esters (POE).

### Customer benefits and product features

- Designed for thermal and chemical stability with hydro fluorocarbon (HFC) refrigerants R134a, R404a and R410A
- Formulated for oil-refrigerant miscibility properties with HFC and FC refrigerants over a wide range of operating temperatures
- Helps provide high performance compressor cleanliness in numerous compressor tests conducted by Chevron
- Promotes minimal copper transfer
- Synthetic lubrication technology

### Applications

- Capella HFC oils have been specifically developed in cooperation with major refrigerant compressor manufacturers worldwide, especially suitable for non-ozone depleting FC/HFC refrigerants, such as R134a, R404A, R507, R410A, R407C. Also suitable for hydrocarbon refrigerants such as propane, polypropylene, and isobutane, and HFO and HFO/HFC refrigerants.
- Capella HFC 170 and HFC 220 are especially suitable for deep-freeze systems operating with R23 and for systems operating with hydrocarbon refrigerants (e.g. propane, polypropylene, isobutene) and R22.
- The Capella HFC series is recommended for hermitical, semi-hermetical and open piston compressors and for screw-type and turbo-compressors.
- Capella HFC oils are especially suited for the first fill and retrofit lubrication of refrigeration compressors in large food retails, industrial systems, air conditioning and heat pump equipment and cooling systems in the transport sector. Capella HFC series are also suitable for hydrocarbon refrigerants, such as propane, polypropylene and isobutane

# Capella® HFC

Synthetic Refrigeration Compressor Oil



## Product maintenance and handling

Capella HFC oils are designed to readily absorb moisture from the surrounding air (hygroscopic behaviour), which can cause system performance problems. Capella HFC packs should be kept sealed until time of use and should not be reused once opened (to protect against atmospheric humidity). The performance of Capella HFC can be influenced by a series of factors, including the specific use, method of application, the operational environment, component pre-treatment, and possible external contamination.

## Typical test data

CAPELLA® HFC	TEST METHOD	RESULTS					
<b>ISO Grade</b>		<b>32</b>	<b>55</b>	<b>68</b>	<b>100</b>	<b>170</b>	<b>220</b>
<b>Product Code</b>		<b>560570</b>	<b>565020</b>	<b>560427</b>	<b>560573</b>	<b>560574</b>	<b>560575</b>
Viscosity Index	ASTM D2270	140	138	0.972	0.9704	0.972	0.976
Density, kg/L @ 15°C	ASTM D4052	1.005	1.011	0.972	100.0	173	220
Pour Point, °C	ASTM D97	-48	-39	-39	-30	-27	-27
Flash Point, COC °C	ASTM D92	>240	>240	250	266	260	294
Viscosity, Kinematic,							
mm <sup>2</sup> /s @ 40°C	ASTM D445	32	53	68	100	173	220
mm <sup>2</sup> /s @ 100°C	ASTM D445	5.70	8.40	8.9	11.4	17.1	19.0

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Capella HFC-EN-MEA-v2-100325



**Chevron company product**

© 2025 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.