

Delo[®] 400 SNG SAE 15W-40

Premium mobile gas engine oil



Product description

Delo[®] 400 SNG SAE 15W-40 with ISOSYN[®] Technology is a premium heavy-duty engine oil specifically formulated for spark-ignited natural gas engines operating on CNG, LNG, and LPG. It is designed to help deliver reliable engine protection, excellent cleanliness, and long oil service capability under the operating conditions typical of natural gas combustion.

Delo 400 SNG SAE 15W-40 is formulated with a combination of high-quality base oils and a low-ash additive system, offering resistance to oxidation and nitration while helping to control engine deposits. This enables Delo 400 SNG to help contribute towards extended oil drain intervals and consistent performance in medium- and heavy-duty natural gas engine applications.

Customer benefits

- **Optimized for natural gas engines**
Specifically formulated for CNG, LNG, and LPG-fuelled spark-ignition engines to help deliver dependable performance in medium- and heavy-duty natural gas vehicle applications.
- **Good engine cleanliness**
The low-ash formulation helps deliver excellent sludge and engine deposit control, helping to maintain cleaner pistons, valves, and combustion chambers in natural gas engines operating under high-temperature conditions.
- **Reliable wear protection**
Engineered to provide effective protection for critical engine components, including liners and piston rings, supporting engine durability and helping to reduce wear in demanding natural gas engine operations.
- **Extended oil service capability**
Offers good oxidation and nitration resistance, helping to enable reliable performance over extended oil drain intervals, even under the high thermal and nitration stress associated with natural gas combustion.

Delo[®] 400 SNG SAE 15W-40

Premium mobile gas engine oil



Applications

- Commercial road transport, spark-ignition natural gas engines operating on compressed natural gas (CNG), liquefied natural gas (LNG), or liquefied petroleum gas (LPG).
- It is suitable for a wide range of medium- and heavy-duty mobile applications where reliable engine protection and oil durability are required under high-temperature natural gas combustion conditions.
- Light duty vehicles operating using natural gas (CNG), liquefied natural gas (LNG), or liquefied petroleum gas (LPG).
- Suitable for usage for CNG, LNG, or LPG equipment from many European, North American and/or Japanese OEMs.

Product approvals, performance and recommendations

DELO [®] 400 SNG	SAE 15W-40
Cummins CES 20092	Approved
Detroit Diesel (Daimler Truck) 93K216	Meets the requirements

DeLo[®] 400 SNG SAE 15W-40

Premium mobile gas engine oil



Typical test data

DELO [®] 400 SNG	TEST METHOD	RESULT
SAE Grade		15W-40
Product Code		235114
Base Number, mg KOH/g	ASTM D2896	7.0
Density, 15 kg/L	ASTM D4052	0.8705
Kinematic Viscosity, mm ² /s @ 40°C	ASTM D445	115.0
mm ² /s @ 100°C	ASTM D445	15.40
Viscosity Index	ASTM D2270	140
Pour Point, °C	ASTM D97	-36
Flash Point, COC °C	ASTM D92	238
Sulfated Ash, mass %	ASTM D874	0.89

0226

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Safety Data Sheet (SDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain an SDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

Customers should always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

DELO 400 SNG SAE 15W-40-MEA-v2-070426



Chevron company product

© 2026 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.