

# Taro Ultra 140A

Low-speed engine oil



## Product description

**Taro® Ultra 140A** is a new range of cylinder lubricants specifically designed to cope with the demands and required flexibility for IMO 2020. Taro Ultra cylinder lubricants have been fully field tested using a wide variety of post-IMO 2020 fuel types and are approved by major OEMs.

**Taro Ultra 140A** is a 140 Base Number (BN) cylinder oil specially formulated for use in high corrosion environments. As an ultra-high base number cylinder lubricant, this product is created for the latest type of highly efficient two-stroke / low-speed crosshead engines which have an increased tendency to develop cold corrosion inside the cylinder than the older, less efficient installations.

## Customer benefits and product features

### Customer benefits

- **Engine protection**  
Effective acid neutralization helps ensure protection against excessive cylinder liner and piston ring wear resulting from the use of high sulphur heavy fuel oils to help extend cylinder liner and piston ring life.
- **Engine cleanliness**  
Designed to prevent ring sticking and help minimize deposit formation on the pistons and throughout the combustion chamber exhaust areas.
- **Storage stability**  
Stable at ambient temperature and during long-term storage.
- **Compatibility**  
Compatible with diesel cylinder lubricants generally known to the international marine trade.
- **Operating cost**  
Ultra-high base number formulation helps to provide the same level of alkalinity and corrosion protection at lower feed rates, offering reduced operating costs.

### Product features

- Taro Ultra 140A provides the same level of alkalinity and corrosion protection as Taro Ultra 100 at lower feedrates, therefore helping to reduce operating costs.
- Taro Ultra 140A is blended with highly refined base oils and carefully selected additives to provide excellent ring and liner wear protection and piston cleanliness in low-speed crosshead diesel engines.

# Taro Ultra 140A

Low-speed engine oil



## Applications

Taro Ultra 140A is recommended for lubricating the cylinders of the latest generation large two-stroke / low-speed crosshead diesel engines equipped with exhaust abatement technologies operating with heavy fuel oil, under all loads and very corrosive operating conditions. The base number of Taro Ultra 140A makes this product ideal for use in engine types and under operating conditions which are sensitive to cold corrosion in the cylinder.

Taro Ultra 140A should be used in accordance with OEM guidelines and recommendations.

## Product approvals, performance and recommendations

TARO® ULTRA 140A	SAE 50
Everllence Large Diesel Engines	A
Winterthur Gas & Diesel Large Diesel Engines	A

A: Approval / No objection letter by OEM

# Taro Ultra 140A

Low-speed engine oil



## Typical test data

TARO® ULTRA 140A	TEST METHOD	RESULT
<b>SAE Grade</b>		<b>50</b>
<b>Product Code</b>		<b>563018</b>
Base Number, mg KOH/g	ASTM D2896	140
Density at 15 °C, (Kg/L)	ASTM D4052	0.98
Flash Point COC, °C	ASTM D92	220 min
Pour Point, °C	ASTM D97	-12
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	ASTM D445	19

0426

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Safety Data Sheet (SDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain an SDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

Customers should always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

TARO® ULTRA 140A/MEA/CHV/PDSv2\_080426



**Chevron company product**

© 2026 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.