



Havoline ProDS PR SAE 0W-20

Premium performance synthetic engine oil

Product description

Havoline® ProDS PR SAE 0W-20 is a premium performance synthetic engine oil specifically formulated with advanced technology additives to meet PSA B71-2010 and Renault RN 17FE engine lubrication requirements.

Havoline ProDS PR SAE 0W-20 is suitable for use in gasoline and diesel passenger cars, light duty commercial diesel engines, and hybrid vehicles. It is a mid SAPS oil compatible with diesel/gasoline particulate filters (DPF/GPF) and three-way catalysts (TWC).

Customer benefits

- Mid SAPS formulation designed to help protect aftertreatment systems from soot and deposit build-up, while helping to minimise exhaust emissions.
- Good low temperature fluidity promotes rapid lubricant circulation during cold starts, contributing to improved engine protection and fuel economy.
- Formulated with advanced cleaning additives to help minimise deposit and sludge build-up.
- Good oxidation and thermal stability helps maintain oil performance throughout the service interval.
- Engineered to provide protection against Low-Speed Pre-Ignition (LSPI), helping to prevent severe engine damage in modern PSA engines.
- Designed for use in hybrid vehicles, with additive technology that helps control the effects of fuel and water dilution, including rust, corrosion, emulsion and wear.
- Synthetic base oil technologies help to reduce oil volatility, contributing to lower oil consumption.

Product highlights

- **Helps protect aftertreatment systems**
- **Offers cold temperature start-up and fuel economy performance**
- **Helps minimise deposits and sludge build-up**
- **Formulated for good oxidation and thermal stability**
- **Provides protection against Low-Speed Pre-Ignition (LSPI)**
- **Designed for use in hybrid vehicles**
- **Helps reduce oil consumption**

Selected specification standards include:

ACEA	API
Fiat	PSA
Renault	

Applications

- Havoline ProDS PR SAE 0W-20 is suitable for use in Euro 6 and later gasoline passenger cars, light diesel vans and hybrid vehicles, with or without turbochargers and equipped with gasoline or diesel particulate filters (GPF/DPF), operating on European fuels.
- Havoline ProDS PR SAE 0W-20 is designed for Euro 6 vehicles requiring PSA B71-2010 and Renault RN17 FE engine oils.
- It is suitable for recent Peugeot and Citroën engines, including DV5R and EB2DT engines, particularly those equipped with BlueHDi, PureTech, Stop & Start technologies and hybrid systems.

Havoline ProDS PR SAE 0W-20 is not suitable for use in some engines. Consult owner manual or handbook if in doubt.

Approvals, performance and suitable for use

Approvals

- Renault RN 17FE

Performance

- ACEA C5
- API SP
- PSA B71-2010

Suitable for use

Havoline ProDS PR SAE 0W-20 is suitable for use in engines requiring:

- Fiat 9.55535-DM1
- Fiat 9.55535-GSX

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 0W-20
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.845
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	8.0
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	41.5
Viscosity Index	ASTM D2270	169
Pour point, °C	ASTM D97	-45
Flash point COC, °C	ASTM D92	233

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see <http://europe.chevronlubricants.com>.

A Chevron company product