Safety Data Sheet



SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Delo 400 LE Synthetic SAE 5W-40

Product Number(s): 803078

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Heavy Duty Motor Oil

1.3 Details of the supplier of the safety data sheet

Chevron Products UK Limited 1 Westferry Circus Canary Wharf London E14 4HA United Kingdom

email: eumsds@chevron.com

1.4 Emergency telephone number

Transportation Emergency Response

Europe: 0044/(0)18 65 407333 and CHEMTREC: +1 703 527 3887

Health Emergency

Chevron Emergency Information Center: Located in the USA, international calls accepted 24 hours: +1

510 231 0623

Europe: 0044/(0)18 65 407333

Product Information

Product Information: FAX number: 0044/20 77 19 5171

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLP CLASSIFICATION:

Not classified as dangerous according to EU regulatory guidelines.

2.2 Label elements

Under the criteria of Regulation (EC) No 1272/2008 (CLP):

Not classified

- contains: Molybdenum polysulfide long chain alkyl dithiocarbamide complex. May

produce an allergic reaction.

2.3 Other hazards

This product is not, or does not contain, a substance that is a potential PBT or a vPvB. This product is not, or does not contain, a substance that potentially has endocrine disrupting properties.

Revision Number: 3 1 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

3.2 Mixtures

This material is a mixture.

COMPONENTS	CAS	EC	REGISTRATION	CLP	AMOUNT
	NUMBER	NUMBER	NUMBER	CLASSIFICATION	
Distillates, hydrotreated	64742-54-7	265-157-1	01-2119484627-25	Asp. Tox. 1/H304	50 - 69
heavy paraffinic					%weight
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	68649-12-7	614-695-9	01-2119527646-33	Asp. Tox. 1/H304	0 - 10 %weight
1-Decene homopolymer hydrogenated	68037-01-4	500-183-1	01-2119486452-34	Asp. Tox. 1/H304	0 - 10 %weight
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29	Asp. Tox. 1/H304	0 - 5 %weight
Zinc bis[O-(6- methylheptyl)] bis[O- (sec-butyl)] bis(dithiophosphate)	93819-94-4	298-577-9	01-2119543726-33	Aquatic Chronic 2/H411; Eye Dam. 1/H318; Skin Irrit. 2/H315	< 2 %weight
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Mixture	457-320-2	01-0000019337-66	Aquatic Chronic 3/H412; Skin Sens. 1B/H317; Skin Irrit. 2/H315	< 1 %weight
Phenol, dodecyl-, branched	121158-58-5	310-154-3	01-2119513207-49	Aquatic Acute 1/H400 [M=10]; Aquatic Chronic 1/H410 [M=10]; Eye Dam. 1/H318; Repr. 1B/H360 [C>=1.5]; Skin Corr. 1C/H314	< 0.25 %weight

The full text of all CLP H-statements is shown in Section 16.

In accordance with the Regulation (EC)No 1272/2008, Nota L, reference IP 346/92: "DMSO Extraction Method", we have determined that the base oils used in this preparation are not carcinogenic.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs. If exposure to hydrogen sulfide (H2S) gas is possible during an emergency, wear an approved, positive pressure air-supplying respirator. Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Revision Number: 3 2 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

4.2 Most important symptoms and effects, both acute and delayed IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to be harmful.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing. Hydrogen sulfide has a strong rotten-egg odor. However, with continued exposure and at high levels, H2S may deaden a person's sense of smell. If the rotten egg odor is no longer noticeable, it may not necessarily mean that exposure has stopped. At low levels, hydrogen sulfide causes irritation of the eyes, nose, and throat. Moderate levels can cause headache, dizziness, nausea, and vomiting, as well as coughing and difficulty breathing. Higher levels can cause shock, convulsions, coma, and death. After a serious exposure, symptoms usually begin immediately.

DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS: Not classified.

4.3 Indication of any immediate medical attention and special treatment needed

Note to Physicians: Administration of 100% oxygen and supportive care is the preferred treatment for poisoning by hydrogen sulfide gas. For additional information on H2S, see Chevron SDS No. 301.

SECTION 5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

5.2 Special hazards arising from the substance or mixture

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Sulfur, Zinc, Phosphorus, Nitrogen.

5.3 Advice for firefighters

This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition in vicinity of spilled material. Refer to Sections 5 and 8 for more information.

6.2 Environmental precautions

Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater.

6.3 Methods and material for containment and cleaning up

Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil and dispose of in a manner consistent with applicable requirements. Place other contaminated materials in disposable containers and dispose of in a manner consistent with applicable requirements. Report spills to local authorities as appropriate or required.

6.4 Reference to other sections

Revision Number: 3 3 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

SECTION 7 HANDLING AND STORAGE

7.1 Precautions for safe handling

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not breathe gas. Wash thoroughly after handling.

Unusual Handling Hazards: Toxic quantities of hydrogen sulfide (H2S) may be present in storage tanks and bulk transport vessels which contain or have contained this material. Persons opening or entering these compartments should first determine if H2S is present. See Exposure Controls/Personal Protection -Section 8. Do not attempt rescue of a person over exposed to H2S without wearing approved suppliedair or self-contained breathing equipment. If there is a potential for exceeding one-half the occupational exposure standard, monitoring of hydrogen sulfide levels is required. Since the sense of smell cannot be relied upon to detect the presence of H2S, the concentration should be measured by the use of fixed or portable devices.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

7.2 Conditions for safe storage, including any incompatibilities Not Applicable

7.3 Specific end use(s): Heavy Duty Motor Oil

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

8.1 Control parameters

Occupational Exposure Limits: No applicable occupational exposure limits exist for this material or its components. Consult local authorities for appropriate values.

8.2 Exposure controls **ENGINEERING CONTROLS:**

Use in a well-ventilated area.

Delo 400 LE Synthetic SAE 5W-40 Revision Number: 3 4 of 13 Revision Date: January 31, 2023 MSDS: 37083

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced. Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	120
Nitrile	0.8	240
Viton Butyl	0.3	240

Respiratory Protection: No respiratory protection is normally required. If material is heated and emits hydrogen sulfide, determine if airborne concentrations are below the occupational exposure limit for hydrogen sulfide. If not, wear an approved positive pressure air-supplying respirator. For more information on hydrogen sulfide, see Chevron SDS No. 301. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

ENVIRONMENTAL EXPOSURE CONTROLS:

See relevant Community environmental protection legislation or the Annex, as applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

9.1 Information on basic physical and chemical properties

Appearance

Color: Brown to yellow Physical State: Liquid Odor: Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Melting Point: No data available Freezing Point: No data available Initial Boiling Point: No data available

Flashpoint: (Cleveland Open Cup) 200 °C (392 °F) (Minimum)

Evaporation Rate: No data available **Flammability (solid, gas):** Not Applicable

Flammability (Explosive) Limits (% by volume in air):

Lower: Not Applicable Upper: Not Applicable

Vapor Pressure: <0.01 mmHg @ 37.8 °C (100 °F)

Vapor Density (Air = 1): >1

Density: 0.8590 kg/l @ 15°C (59°F) (Typical)

Solubility: Soluble in hydrocarbons; insoluble in water **Partition coefficient: n-octanol/water:** No data available

Revision Number: 3 5 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

Auto-ignition temperature: No data available **Decomposition temperature:** No data available **Viscosity:** 14.60 mm2/s @ 100°C (212°F) (Typical)

Explosive Properties: No Data Available **Oxidising properties:** No Data Available

9.2 Other Information: No Data Available

SECTION 10 STABILITY AND REACTIVITY

- **10.1 Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
- **10.2 Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
- 10.3 Possibility of hazardous reactions: Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid: Not applicable
- 10.5 Incompatible materials to avoid: Not applicable
- **10.6 Hazardous decomposition products:** Alkyl Mercaptans (Elevated temperatures), Hydrogen Sulfide (Elevated temperatures)

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Product Information:

Serious Eye Damage/Irritation: The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Corrosion/Irritation: The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Sensitization: The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Dermal Toxicity: The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate (dermal): Not Applicable

Acute Oral Toxicity: The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate (oral): Not Applicable

Acute Inhalation Toxicity: The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate (inhalation): Not Applicable

Germ Cell Mutagenicity: The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Carcinogenicity: The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Reproductive Toxicity: The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Single Exposure: The material is not considered a target organ

Revision Number: 3 6 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Repeated Exposure: The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Aspiration Hazard: The material is not considered an aspiration hazard.

Component Information:

Component information.	
Serious Eye Damage/Irritation:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene,	Based on available data, the classification criteria are not met
trimer, hydrogenated	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
paraffinic	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-	Test Result: Causes serious eye damage
butyl)] bis(dithiophosphate)	* read-across data from similar material
Molybdenum polysulfide long chain alkyl	Based on available data, the classification criteria are not met
dithiocarbamide complex	
Phenol, dodecyl-, branched	Protocol: Eye Irritation
	Test Result: Causes serious eye damage

Skin Corrosion/Irritation:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Test Result: Causes skin irritation * read-across data from similar material
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Test Result: Causes skin irritation
Phenol, dodecyl-, branched	Protocol: OECD 404 - Dermal Irritation/Corrosion Test Result: Causes severe skin burns and eye damage * read-across data from similar material

Skin Sensitization:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Test Result: May cause allergic skin reaction
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Acute Dermal Toxicity:		
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met	
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met	
1-Decene, tetramer, mixed with 1-decene,	Based on available data, the classification criteria are not met	

Delo 400 LE Synthetic SAE 5W-40 MSDS: 37083 **Revision Number:** 3 7 of 13 Revision Date: January 31, 2023

trimer, hydrogenated	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
paraffinic	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-	Based on available data, the classification criteria are not met
butyl)] bis(dithiophosphate)	
Molybdenum polysulfide long chain alkyl	Based on available data, the classification criteria are not met
dithiocarbamide complex	
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Acute Oral Toxicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Acute Inhalation Toxicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Germ Cell Mutagenicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Carcinogenicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene,	Based on available data, the classification criteria are not met
trimer, hydrogenated	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
paraffinic	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-	Based on available data, the classification criteria are not met
butyl)] bis(dithiophosphate)	

Delo 400 LE Synthetic SAE 5W-40 MSDS: 37083 Revision Number: 3 Revision Date: January 31, 2023 8 of 13

Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Reproductive Toxicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec- butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Protocol: OECD 415 - One-Generation Reproduction Toxicity Test Result: May damage fertility or the unborn child if ingested based on animal data
Phenol, dodecyl-, branched	Test Result: May damage fertility or the unborn child if absorbed through skin

Specific Target Organ Toxicity - Single Exposure:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

Specific Target Organ Toxicity - Repeated Exposure:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Based on available data, the classification criteria are not met
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	Based on available data, the classification criteria are not met
Phenol, dodecyl-, branched	Based on available data, the classification criteria are not met

ADDITIONAL TOXICOLOGY INFORMATION:

During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

11.2 Information on other hazards

No other hazards identified.

SECTION 12 ECOLOGICAL INFORMATION

Delo 400 LE Synthetic SAE 5W-40 MSDS: 37083 **Revision Number:** 3 9 of 13 Revision Date: January 31, 2023

Product Information:

12.1 Toxicity

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

12.2 Persistence and degradability

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

12.3 Bioaccumulative potential

Bioconcentration Factor: No Data Available

Octanol/Water Partition Coefficient: No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a potential PBT or a vPvB.

12.6 Endocrine Disrupting Properties

This mixture does not contain any substances that are assessed as having endocrine disrupting properties.

12.7 Other adverse effects

No other adverse effects identified.

Component Information:

A cuto Toxicity	
Acute Toxicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
Distillates (petroleum), hydrotreated light paraffinic	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	Confidential test data
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	No test data available
Phenol, dodecyl-, branched	Confidential test data
Phenol, dodecyl-, branched	Confidential test data

Long-term Toxicity:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-	Based on available data, the classification criteria are not met
decene, trimer, hydrogenated	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
paraffinic	
	No test data available
butyl)] bis(dithiophosphate)	
	Confidential test data
dithiocarbamide complex	
Phenol, dodecyl-, branched	Confidential test data

Biodegradation:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met

Revision Number: 3 10 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-	Based on available data, the classification criteria are not met
decene, trimer, hydrogenated	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
paraffinic	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-	Not applicable
butyl)] bis(dithiophosphate)	
Molybdenum polysulfide long chain alkyl	Test Result: Not readily biodegradable
dithiocarbamide complex	
Phenol, dodecyl-, branched	Protocol: OECD 301B-Modified Sturm
	Test Result: Not readily biodegradable
	Biodegradation: 25%W

Bioaccumulative Potential:	
Distillates, hydrotreated heavy paraffinic	Based on available data, the classification criteria are not met
1-Decene homopolymer hydrogenated	Based on available data, the classification criteria are not met
1-Decene, tetramer, mixed with 1-decene, trimer, hydrogenated	Based on available data, the classification criteria are not met
, ,	Based on available data, the classification criteria are not met
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	No test data available
Molybdenum polysulfide long chain alkyl dithiocarbamide complex	No test data available
	No test data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

In accordance with European Waste Catalogue (E.W.C.) the codification is the following: 13 02 06

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantityspecific shipping requirements.

ADR/RID

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN Number or ID Number: Not applicable 14.2 UN proper shipping name: Not applicable 14.3 Transport hazard class(es): Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable 14.6 Special precautions for user: Not applicable

ICAO / IATA

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN Number or ID Number: Not applicable 14.2 UN proper shipping name: Not applicable 14.3 Transport hazard class(es): Not applicable

Revision Number: 3 Delo 400 LE Synthetic SAE 5W-40 11 of 13 Revision Date: January 31, 2023

MSDS: 37083

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable **14.6 Special precautions for user:** Not applicable

IMO / IMDG

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN Number or ID Number: Not applicable 14.2 UN proper shipping name: Not applicable 14.3 Transport hazard class(es): Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

14.7 Maritime Transport in Bulk according to IMO Instruments: Not applicable

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REGULATORY LISTS SEARCHED:

01=EU Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances.

02=EU Directive 90/394/EEC: Carcinogens at work.

03=EU Directive 92/85/EEC: Pregnant or breastfeeding workers.

04=EU Directive 2012/18/EU: Seveso III.

05=EU Directive 98/24/EC: Chemical agents at work.

06=EU Directive 2004/37/EC: On the protection of workers.

07=EU Regulation EC No. 689/2008: Annex 1, Part 1.

08=EU Regulation EC No. 689/2008: Annex 1, Part 2.

09=EU Regulation EC No. 689/2008: Annex 1, Part 3.

10=EU Regulation EC No. 850/2004: Prohibiting and restricting persistent organic pollutants (POPs).

11=EU REACH, Annex XVII: Restrictions on manufacture, placing on the market and use of certain dangerous substances, mixture & article.

12=EU REACH, Annex XIV: Authorization List or Candidate List of Substances of Very High Concern for Authorization (SVHC).

The following components of this material are found on the regulatory lists indicated.

Distillates, hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Phenol, dodecyl-, branched

03, 05, 11

03, 05, 11

03, 05, 11

03, 05, 11

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AIIC (Australia), DSL (Canada), ENCS (Japan), KECI (Korea), NZIoC (New Zealand), TCSI (Taiwan), TSCA (United States).

15.2 Chemical safety assessment

No chemical safety assessment.

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: SECTION 01 - Health Emergency information was modified.

SECTION 02 - Supplemental Hazard information was modified.

SECTION 03 - Base Oil Registration Number List information was deleted.

SECTION 03 - Composition information was modified.

SECTION 05 - Special hazards arising from the substance or mixture information was modified.

SECTION 08 - Eye/Face Protection information was modified.

SECTION 08 - General Considerations information was modified.

SECTION 08 - Occupational Exposure Limit Table information was deleted.

SECTION 08 - Personal Protective Equipment List information was deleted.

Revision Number: 3 12 of 13 Delo 400 LE Synthetic SAE 5W-40 Revision Date: January 31, 2023 MSDS: 37083

SECTION 08 - Personal Protective Equipment information was added.

SECTION 08 - Respiratory Protection information was modified.

SECTION 08 - Skin Protection information was modified.

SECTION 09 - Physical/Chemical Properties information was modified.

SECTION 11 - Toxicological Information information was modified.

SECTION 11.2 - Other Hazards information was added.

SECTION 12 - Ecological Information information was modified.

SECTION 12.6 - Endocrine Disrupting Properties information was added.

SECTION 15 - Chemical Inventories information was modified.

SECTION 15 - Regulatory Information information was added.

SECTION 15 - Regulatory Information information was modified.

SECTION 16 - Full Text of H-Statements information was modified.

Revision Date: January 31, 2023

Full text of CLP H-statements:

Asp. Tox. 1/H304; May be fatal if swallowed and enters airways

Aguatic Acute 1/H400; Very toxic to aquatic life

Aquatic Chronic 1/H410; Very toxic to aquatic life with long lasting effects

Aquatic Chronic 2/H411; Toxic to aquatic life with long lasting effects

Aguatic Chronic 3/H412; Harmful to aquatic life with long lasting effects

Eye Dam. 1/H318; Causes serious eye damage

Repr. 1B/H360; May damage fertility or the unborn child

Skin Sens. 1/H317; May cause an allergic skin reaction

Skin Corr. 1C/H314; Causes severe skin burns and eye damage

Skin Irrit. 2/H315; Causes skin irritation

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
CVX - Chevron	CAS - Chemical Abstract Service Number
NQ - Not Quantifiable	

Prepared according to the EU Regulation 1907/2006 (as amended) by Chevron Technical Center, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

No Annex

Revision Number: 3 13 of 13 Delo 400 LE Synthetic SAE 5W-40

MSDS: 37083