

# Safety Data Sheet



## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

### DispoRack

**Product Use:** Specialty Product  
**Product Number(s):** 955320, 999993

**Company Identification**  
Chevron Singapore Pte Ltd  
3 Fraser Street #12-28  
DUO Tower  
Singapore 189352

**Transportation Emergency Response**  
Singapore Civil Defense Force: 995

**Health Emergency**  
Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

**Product Information**  
Product Information: +65-6318-1000  
SDS Requests: +65-6318-1000

## SECTION 2 HAZARDS IDENTIFICATION

### CLASSIFICATION:

- Flammable liquid: Category 2.
- Aspiration toxicant: Category 1.
- Serious eye damage: Category 1.
- Skin corrosion: Category 1B.
- Target organ toxicant (central nervous system): Category 3.
- Acute aquatic toxicant: Category 1.
- Chronic aquatic toxicant: Category 1.



**Signal Word:** Danger

### Physical Hazards:

- Highly flammable liquid and vapour (H225).

### Health Hazards:

- May be fatal if swallowed and enters airways (H304).
- Causes severe skin burns and eye damage (H314).
- May cause drowsiness or dizziness (H336).

### Environmental Hazards:

- Very toxic to aquatic life with long lasting effects (H410).

## PRECAUTIONARY STATEMENTS:

### Prevention:

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking (P210).
- Keep container tightly closed (P233).
- Keep cool (P235).
- Ground and bond container and receiving equipment (P240).
- Use explosion-proof electrical, ventilating, lighting, and equipment (P241).
- Use only non-sparking tools (P242).
- Take precautionary measures against static discharge (P243).
- Do not breathe dust/fume/gas/mist/vapours/spray (P260).
- Wash thoroughly after handling (P264).
- Use only outdoors or in a well-ventilated area (P271).
- Avoid release to the environment (P273).
- Wear protective gloves/protective clothing/eye protection/face protection (P280).

### Response:

- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting (P301+P330+P331).
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower (P303+P361+P353).
- IF INHALED: Remove person to fresh air and keep comfortable for breathing (P304+P340).
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing (P305+P351+P338).
- Immediately call a POISON CENTER, doctor, or physician (P310).
- Specific treatment (see Notes to Physician on this label) (P321).
- Wash contaminated clothing before reuse (P363).
- In case of fire: Use media specified in the SDS to extinguish (P370+P378).
- Collect spillage (P391).

### Storage:

- Store in a well-ventilated place. Keep container tightly closed (P403+P233).
- Store locked up (P405).

### Disposal:

- Dispose of contents and container in accordance with applicable local, regional, national, and international regulations (P501).

**HAZARDS OTHERWISE NOT CLASSIFIED:** Not applicable.

## SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Acetone	67-64-1	30 - 50 %weight
Octane	111-65-9	10 - 30 %weight
Acetic acid	64-19-7	1 - 15 %weight

## SECTION 4 FIRST AID MEASURES

**Eye:** Flush eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get immediate medical attention.

**Skin:** Wash skin with water immediately and remove contaminated clothing and shoes. Get immediate medical attention. To further remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

**Inhalation:** Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue or if any other symptoms

develop.

### **IMMEDIATE HEALTH EFFECTS**

**Eye:** Causes serious eye damage. Symptoms may include pain, tearing, reddening, swelling and impaired vision.

**Skin:** Contact with the skin causes permanent damage, including burns and scarring. Skin contact may cause drying or defatting of the skin. Symptoms may include pain, itching, discoloration, swelling, and blistering. Contact with the skin is not expected to cause an allergic skin response.

**Ingestion:** Highly toxic; may be fatal if swallowed. Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death. May be severely irritating and cause permanent damage to the mouth, throat, and stomach. Symptoms may include pain, nausea, vomiting, diarrhea, and, in severe cases, collapse, shock, and death.

**Inhalation:** Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death. If this material is heated, fumes may be unpleasant and produce nausea and irritation of the eye and upper respiratory tract.

**Note to Physicians:** Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis. Probable mucosal damage may contraindicate the use of gastric lavage.

## **SECTION 5 FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Unusual Fire Hazards:** See Section 7 for proper handling and storage.

### **PROTECTION OF FIRE FIGHTERS:**

**Fire Fighting Instructions:** For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

**Protective Measures:** Observe all relevant local and international regulations. Eliminate all sources of ignition in the vicinity of the spill or released vapor. If this material is released into the work area, evacuate the area immediately. Monitor area with combustible gas indicator. Keep out unnecessary and unprotected personnel. Persons entering the contaminated area to correct the problem or to determine whether it is safe to resume normal activities must comply with all instructions in the Exposure Controls/Personal Protection section.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. All equipment used when handling the product must be grounded. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

**Reporting:** Report spills to local authorities as appropriate or required.

## SECTION 7 HANDLING AND STORAGE

**General Handling Information:** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Precautionary Measures:** This material presents a fire hazard. Liquid quickly evaporates and forms vapor (fumes) which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources such as pilot lights, welding equipment, and electrical motors and switches. Fire hazard is greater as liquid temperature rises above -10C (15F). Do not get in eyes, on skin, or on clothing. Do not breathe vapor or fumes from heated material. Do not taste or swallow. Wash thoroughly after handling.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

**General Storage Information:** DO NOT USE OR STORE near heat, sparks, flames, or hot surfaces . USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

### ENGINEERING CONTROLS:

Use general ventilation, local exhaust ventilation, or a combination of both.

### PERSONAL PROTECTIVE EQUIPMENT

**Eye/Face Protection:** Wear protective equipment to prevent eye contact. Selection of protective equipment may include: indirect vented goggles, non-vented (closed) goggles, and a combination of chemical goggles with face shield, depending upon the work operations conducted.

**Skin Protection:** Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. **Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced.** Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	240
Neoprene	0.9	68

Nitrile	0.85	25
Polyvinyl Chloride (PVC)	1.1	30
Viton Butyl	0.3	120

**Respiratory Protection:** A site-specific risk assessment should be conducted by an Occupational Hygienist or a Safety Professional to determine the type and use of respiratory protective equipment. When a site-specific risk assessment determines that respiratory protection is required, use an approved respirator such as:

**Air purifying respirator -**

If airborne concentration limits exceed the applicable occupational exposure limit, but are below the maximum use concentration.

Vapors only: organic vapor cartridge (filter type A3 per EN 529:2005).

Vapors and particulates (including generated mists): both an organic vapor cartridge & particulate filter (AP3 filter per EN 529:2005).

Refer to respirator manufacturers to obtain service life of cartridge / filter.

**Positive pressure air-supplying respirator -**

If airborne concentration limits exceed the maximum use concentration offered from an air purifying respirator.

Refer to EN 529:2005, USA OSHA 1910.134, and/or other applicable local/regional/national/international standards for regulatory requirements.

**Occupational Exposure Limits:**

Component	Country/ Agency	Form	TWA	STEL	Ceiling	Notation
Acetone	ACGIH	--	250 ppm	500 ppm	--	--
Acetone	Singapore	--	1780 mg/m3	2380 mg/m3	--	--
Octane	ACGIH	--	300 ppm	--	--	--
Octane	Singapore	--	1400 mg/m3	1750 mg/m3	--	--
Acetic acid	ACGIH	--	10 ppm	15 ppm	--	--
Acetic acid	Singapore	--	25 mg/m3	37 mg/m3	--	--

Consult local authorities for appropriate values.

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

**Attention: the data below are typical values and do not constitute a specification.**

**Color:** Colorless

**Physical State:** Liquid

**Odor:** Characteristic

**Odor Threshold:** No data available

**pH:** No data available

**Vapor Pressure:** 11 mmHg - 184 mmHg @ 20 °C (68 °F)

**Relative Vapor Density:** No data available

**Boiling Point:** 50°C (122°F) (Minimum)

**Solubility:** Soluble in water.

**Freezing Point:** No data available

**Melting Point:** No data available

**Particle Characteristics:** Not applicable

**Density:** 0.7 g/cm3 - 1 g/cm3 @ 15°C (59°F)

**Kinematic Viscosity:** No data available

**Evaporation Rate:** No data available

**Partition coefficient n-octanol/water (logarithmic value):** No data available

**FLAMMABLE PROPERTIES:**

**Flashpoint:** (Closed Cup) < 21 °C (< 70 °F)

**Autoignition:** > 220 °C (> 428 °F)

**Flammability (Explosive) Limits (% by volume in air):** Lower: No data available Upper: No data available

**SECTION 10 STABILITY AND REACTIVITY**

**Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Incompatibility With Other Materials:** Not applicable

**Hazardous Decomposition Products:** None known (None expected)

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**SECTION 11 TOXICOLOGICAL INFORMATION**

**Eye Irritation:** This material causes serious eye damage. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Dermal Toxicity:** The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for product components.

**Skin Irritation:** This material causes severe skin burns and eye damage. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Skin Sensitization:** The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for product components.

**Acute Oral Toxicity:** The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for product components.

**Acute Inhalation Toxicity:** The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for product components.

**Acute Toxicity Estimate:** Not Determined

**Germ Cell Mutagenicity:** The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Carcinogenicity:** The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Reproductive Toxicity:** The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Single Exposure:** This material may cause drowsiness or dizziness. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Repeated Exposure:** The material is not considered a target organ

toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Aspiration Hazard:** This material is considered an aspiration hazard based on the kinematic viscosity of the material.

## SECTION 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

This material is expected to be very toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

The product has not been tested. The statement has been derived from the properties of the individual components.

### MOBILITY

No data available.

### PERSISTENCE AND DEGRADABILITY

This material is expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

### POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Partition coefficient n-octanol/water (logarithmic value): No data available

### Other adverse effects

No other adverse effects identified.

## SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations.

## SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**DOT Shipping Description:** UN2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Acetone, Octane and Acetic acid), 3 (8), II, MARINE POLLUTANT (Octane)

**IMO/IMDG Shipping Description:** UN2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Acetone, Octane and Acetic acid), 3 (8), II, MARINE POLLUTANT (Octane)

**ICAO/IATA Shipping Description:** UN2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Acetone, Octane and Acetic acid), 3 (8), II, MARINE POLLUTANT (Octane)

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:** Not applicable

## SECTION 15 REGULATORY INFORMATION

### REGULATORY LISTS SEARCHED:

01-1=IARC Group 1

01-2A=IARC Group 2A  
01-2B=IARC Group 2B  
02=Singapore, Hazardous Substances Control List

The following components of this material are found on the regulatory lists indicated.  
Acetic acid 02

**CHEMICAL INVENTORIES:**

All components comply with the following chemical inventory requirements: DSL (Canada), EINECS (European Union), IECSC (China), TCSI (Taiwan), TSCA (United States).

**SECTION 16 OTHER INFORMATION**

**REVISION STATEMENT:** SECTION 01 - Health Emergency information was modified.  
SECTION 04 - First Aid - Skin information was modified.  
SECTION 11 - Immediate Health Effects - Eye information was modified.  
SECTION 15 - Regulatory Information information was added.

**Revision Date:** May 06, 2026

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental Industrial Hygienists	IMO/IMDG - International Maritime Dangerous Goods Code
API - American Petroleum Institute	SDS - Safety Data Sheet
CVX - Chevron	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration

Prepared according to the Singapore Standard SS 586:3 2022

**The information in this SDS is based on the knowledge, information, and belief of Chevron and its affiliates as of the publication date. It is not a quality specification, and no warranty, express or implied, is given. We assume no responsibility or liability for the results of using this material. The information presented here pertains only to the listed product. Since conditions of use are beyond our control, it is the user's responsibility to determine the conditions for safe use of this product and assess its suitability for their application. Users should seek additional guidance if necessary.**