

Super Outboard 3

Two-Stroke Outboard Motor Oil



Product description

Super Outboard 3 is a premium performance, two-stroke, marine outboard motor oil formulated with a special ashless additive system.

Customer benefits and product features

Customer benefits

- **Maintains high power output**
Special blend of highly refined mineral oil and ashless additive system provides superior piston cleanliness and protection against ring sticking by minimizing deposit formation, thus maintaining combustion efficiency and protecting against power loss.
- **Reduces maintenance costs**
Special ashless additive system includes a selected synthetic component for enhanced lubricity to separate contacting surfaces with a tough lubricant film to protect against wear under high speed, peak performance conditions.
- **Trouble-free operation**
Ashless additive system ensures that ash-induced deposits are not formed in the combustion chamber, thereby eliminating the risk of destructive pre-ignition from this source.
- **Maximizes spark plug life**
Ashless additive system reduces spark plug fouling under all operating conditions.

Product features

- Super Outboard 3 is prediluted with a high flash point, low aromatic content solvent to facilitate mixing with gasoline at all temperatures.
- Super Outboard 3 is designed for engines requiring NMMA TC-W3® certified lubricants, operating in all service conditions.

Super Outboard 3

Two-Stroke Outboard Motor Oil



Applications

- All water-cooled, two-stroke, marine outboard engines, including the latest designs under warranty protection.
- Oil-injected engines.
- Oil-gasoline premix engines at all gasoline-to-oil ratios up to and including 100:1.
- Air-cooled, two-stroke engines where API TD or NMMA certified oils are specified.

Approvals, performance and recommendations

Performance standards

- National Marine Manufacturers Association (NMMA) TC-W3® Certified.
(NMMA TC-W3 Certification Number: RL00420J)

Super Outboard 3

Two-Stroke Outboard Motor Oil



Typical test data

SUPER OUTBOARD 3	
SAE Grade (J1536)	F/M 3
Product Code	560319
Ash, m%	<0.01
Flash Point, PMCC, °C	102
Pour Point, °C	-39
Viscosity	
mm ² /s @ 40°C	56.2
mm ² /s @ 100°C	9.13

1205

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Super Outboard 3/Asia Pacific/CHV/PDSv1_04/2024



A Chevron company product

© 2024 Chevron Products Company. Asia Pacific.
All Rights Reserved.