

Product description

Meropa® oils are high performance, mild EP, industrial gear lubricant formulated with a sulfurphosphorus additive system, which also provides rust and oxidation inhibition, a corrosion and oxidation inhibitor and a metal passivator.

Meropa is specifically designed primarily for industrial gear lubrication services where loads and shock loadings are high.

Customer benefits

- **Maintains gear set efficiencies**
High thermal stability EP system maintains clean gear and bearing surfaces, minimizing deposits which interfere with effective lubrication. High oxidation stability limits in-service viscosity increases, which lead to energy losses.
- **Protects metal surfaces**
Extremely effective EP system forms a protective film in areas of metal-to-metal contact, minimizing wear rates and maintaining efficient transfer of power. Good water separation and effective rust inhibitors protect surfaces against rust and corrosion. High thermal stability additive system reduces the formation of high temperature compounds which can be corrosive to bearing materials. The effective corrosion inhibitor provides additional protection for metal components.
- **Effective oxidation stability**
Effective oxidation inhibitors and copper passivator minimize oil oxidation, limiting viscosity increase and can extend oil drain intervals.

Applications

Can include:

- Enclosed industrial gear drives.
- Open gear drives (heavy grades).
- Spur, bevel, helical, worm and industrial hypoid gear cases.
- Industrial type reduction gearboxes on mining equipment, cement mills, ball and rolling mills, crushers, conveyors, kilns, winches, machine tools and marine equipment.
- Chain drives, sprockets, slide guides and flexible couplings.
- Plain and rolling element bearings.
- For bath, splash, circulation or spray lubrication, as applicable to the grade.

Approvals, performance and recommendations

- ANSI/AGMA 9005-E02 EP
- AIST 224 (formerly U.S. Steel 224) (Grades 68 to 320)
- David Brown, Table E, approved (Grades 68 to 1000)
- DIN 51517 Part 3 CLP (Grades 68 to 680)

Typical test data

MEROPA®	RESULT								
ISO Grade	68	100	150	220	320	460	680	1000	3200
Product Code	530400	530409	530401	530402	530403	530404	530405	530406	530408
(Former) AGMA Lubricant No	2EP	3EP	4EP	5EP	6EP	7EP	8EP	9EP	10EP
David Brown Grade	2E	3E	4E	5E	6E	7E	8E	9E	—
FZG Pass Stage	12	12	12	12	12	12	12	12	12
Pour point, °C	-15	-15	-15	-15	-15	-15	-12	-3	0
Timken OK Load, kg	31.8	31.8	31.8	34.0	34.0	34.0	34.0	34.0	34.0
Viscosity, mm ² /s @ 40°C	68	100	150	220	320	439	650	955	3050
mm ² /s @ 100°C	8.8	11.4	14.9	19.2	24.3	29.8	36.5	44.0	—
Viscosity Index	101	100	99	98	97	96	91	85	—

1508

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.