



# Havoline® Power 2T

## Two-Stroke Motorcycle Oil

Product Data Sheet

### Customer benefits

#### **Reduces exhaust smoke**

Superior combustion characteristics of the special blend of synthetic component and highly refined mineral oil significantly reduce visible smoke in exhaust emissions.

#### **Longer spark plug life**

Low ash additive system reduces spark plug fouling under all operating conditions.

### Applications

- Air and liquid-cooled two-stroke motorcycle engines
- Motorcycle engines that require JASO FC performance oils.
- Two-stroke scooter engines
- Oil-injected engines (except marine outboard) where no fuel/oil premixing is required
- Air-cooled, oil-gasoline premix engines at manufacturers' recommended gasoline-to-oil ratios, up to 50:1
- Two-stroke motorcycle and motor tricycle engines fitted with exhaust catalysts

*Not recommended for use in any marine outboard engines.*

*Not recommended for use in any CNG- or LPG-fuelled two-stroke engines.*

### Product features:

- **Havoline®Power 2T** is a "low smoke", semi-synthetic two-stroke motorcycle oil formulated with a low ash additive system.
- **Havoline®Power 2T** is prediluted with a high flash point, low odor solvent to facilitate mixing with gasoline at all temperatures.
- **Havoline®Power 2T** is designed for engines requiring JASO FC performance lubricants.



## Product specifications

HAVOLINE®POWER 2T	
KEY PROPERTIES	
SAE Grade	F/M 2
Product Code	500708
Flash Point PMCC, °C	98
Pour Point, °C	-15
Sulfated Ash, mass %	0.08
Viscosity,	
mm <sup>2</sup> /s @ 40°C	57.3
mm <sup>2</sup> /s @ 100°C	8.79

## ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: [www.caltexoils.com](http://www.caltexoils.com).

1009

## Performance standards

- JASO FC  
JASO Identification Number: 061CTC663
- ISO EGC
- TIS 1040-2541

## Service Consideration

Havoline Power 2T is not recommended for use in marine outboard engines, chainsaw engines or any CNG- or LPG-fuelled two-stroke engines.

Havoline Power 2T is not recommended for use in any applications where API TC performance oils are required.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:  
**Chevron Global Lubricants**  
– Asia Pacific