



Havoline® Ultra R SAE 5W-30

High performance low SAPS synthetic engine oil

Product description

Havoline Ultra R SAE 5W-30 is a high performance low SAPS synthetic engine oil formulation with an additive package designed to meet MB 226.51 and Renault RN 0720 engine lubrication requirements. In addition to ACEA C4, this product also covers the broader range of ACEA C3 applications.

Havoline Ultra R SAE 5W-30 is formulated with synthetic base oils in combination with an advanced additive system and viscosity index (VI) improver designed to offer reliable long-life engine protection and performance in gasoline and diesel passenger cars and diesel light vans, with three way catalysts (TWC) or diesel particulate filters (DPF).

Customer benefits

- Advanced technology cleaning additives offer oxidation control, wear protection, cleanliness and acid neutralisation and help extend engine life in severe driving conditions
- Low SAPS design helps protect TWCs and DPFs, offering reduced exhaust emissions, optimised system performance and service life
- Premium synthetic base oils with advanced additive technology offer good TBN retention and viscosity increase control
- Robust anti-wear additive technology designed for reliable engine wear protection
- Low temperature fluidity aids rapid lubricant circulation during cold engine starts, offering increased engine protection

Product highlights

- **Designed to extend engine life in severe conditions**
- **Low SAPS helps protect TWCs and DPFs**
- **Offers good TBN retention and viscosity increase control**
- **Formulated for reliable engine wear protection**
- **Aids cold engine start protection**

Selected specification standards include:

ACEA	Mercedes Benz
Renault	

Applications

- Havoline Ultra R SAE 5W-30 is suitable for gasoline and diesel passenger cars or light diesel vans - with or without turbochargers. It is specifically designed for ACEA C4, typically used by Renault, in addition to ACEA C3
- Havoline Ultra R SAE 5W-30 is designed for Renault RN 0720 diesel engines. Daimler also adopted this oil for engines that require a MB 226.51 specification, and in addition this oil can now also be used for MB 229.51 applications

Havoline Ultra R SAE 5W-30 is unsuitable for some engines. Consult owners' manual or handbook if in doubt

Approvals, performance and recommendations

Approvals

- Renault RN 0720

Performance

Havoline Ultra R 5W-30 meets:

- ACEA C4, C3
- Mercedes Benz MB 226.51, MB 229.51

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density, 15°C, kg/l	ASTM D4052	0.85
Visc, Kinematic, 40°C, mm ² /s	ASTM D445	67.5
Visc, Kinematic, 100°C, mm ² /s	ASTM D445	11.7
Viscosity Index	ASTM D2270	170
Pour Point, °C	ASTM D5950	-39
Flash Point COC, °C	ASTM D92	234

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product