

Havoline® Formula SAE 20W-50

Passenger Car Motor Oil



Product description

Havoline® Formula is a highly shear-stable multigrade gasoline engine oil formulated from selected base fluids for use in passenger car and light truck engines requiring API SP or lower performance lubricants.

Customer benefits and product features

Customer benefits

- **Protection against Low Speed Pre Ignition (LSPI) events**
Specially formulated to help protect against LSPI occurrence in turbocharged and/or newer gasoline direct-injection vehicles, which over time helps reduce engine damage.
- **Long engine life**
Proven metallo-organic anti-wear additive system helps protect engines under all operating conditions by providing excellent wear control. Multigrade viscosity provides additional protection against wear under high temperature operating conditions.
- **Maintains high power and performance**
Metallic detergent and ashless dispersant additive system helps maintain high power and performance by providing excellent control of piston and ring deposits under high temperature conditions.
- **Saves on maintenance costs**
High thermal stability and oxidation resistance provides excellent protection against in-service oil degradation that contributes to filter blocking and sludge formation in the oil galleries, crankcase and valve train.
- **Low oil consumption**
Highly shear-stable viscosity index improver helps control oil flow through the piston rings by maintaining high-temperature oil viscosity within the ring belt area in all services.

Product features

- Havoline® with Deposit Shield™ is an advanced detergent formula that helps prevent deposit build up for improved oil stability and increased engine durability.
- Havoline® with Deposit Shield™ provides excellent viscosity control that helps maintain engine power and preserve fuel economy.

Havoline[®] Formula SAE 20W-50

Passenger Car Motor Oil



Applications

- Naturally aspirated gasoline engines in passenger cars and light commercial vehicles.
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

Not recommended for use in engines that require ILSAC or ACEA-classified oils, in turbocharged engines, in CNG or LPG-fuelled engines, in any diesel engines or in motorcycle engines.

Product approvals, performance and recommendations

Performance

- API SP (licensed)

Havoline[®] Formula SAE 20W-50

Passenger Car Motor Oil



Typical test data

HAVOLINE [®] FORMULA SAE 20W-50	RESULTS
SAE Grade	20W-50
Product Code	500010
Base No., D2896, mg KOH/g	7.1
Phosphorus, m %	0.07
Sulfated Ash, m %	0.7
Viscosity, mm ² /s @ 40°C mm ² /s @ 100°C	154 18.4
Viscosity Index	129
Zinc, m%	0.08

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center

[Visit Product Information Center >](#)

Havoline[®] Formula SAE 20W-50/Asia Pacific/CHV/PDSv1_03/2024



A Chevron company product

© 2024 Chevron Products Company. Asia Pacific.
All Rights Reserved.