



# Havoline® Plus 2T

Proven performance two-stroke motor cycle oil

Product Data Sheet

## Product description

Havoline Plus 2T is a mineral-based two-stroke motor oil formulated with a low ash additive system, where JASO FB performance oils are acceptable.

## Customer benefits

- Good lubricity characteristics help protect against friction, engine wear, scuffing and offer increased engine life
- Low ash additive system helps to reduce spark plug fouling, thus increasing spark plug service life. Pre-diluted with a low volatility, low odour solvent to offer easy mixing with gasoline at a wide range of temperatures
- Designed for use in a range of older engines where JASO FB or ISO EGB or lower performance lubricants are acceptable

## Applications

- Air and liquid-cooled two-stroke motorcycle and tricycle engines without exhaust catalyts, where JASO FB performance oils are acceptable
- Two-stroke engines fitted to small portable power equipment (excluding chainsaws) where JASO FB performance oils are acceptable
- Oil-injected engines in land-based service where no fuel/oil premixing is required and where JASO FB performance oils are acceptable
- Air-cooled, oil-gasoline premix engines at manufacturers' recommended gasoline-to-oil ratios, up to 50:1, and where JASO FB performance oils are acceptable

*Not recommended for use in modern motorcycles where low-smoke, JASO FC performance oils are required*

*Not recommended for use in any marine outboard engines*


*Not recommended for use in any engines equipped with exhaust catalyts*

*Not recommended for use in any CNG- or LPG-fuelled two-stroke engines*

## Product highlights:

- Reliable engine protection
- Long sparkplug life
- Formulated for ease-of-use
- Designed to protect older engines

A Chevron company product



## Service considerations

- Havoline Plus 2T is not recommended for use in modern motorcycles, typically those manufactured in the last 10 to 15 years, where low smoke, JASO FC performance oils are required
- Havoline Plus 2T is not recommended for use in marine outboard engines, chainsaw engines, any CNG- or LPG-fuelled two-stroke engines, or any two-stroke engines equipped with exhaust catalyst systems. Proper catalyst protection requires the use of part-synthetic, low-smoke oils in the JASO FC performance class, such as Havoline Super 2T
- Havoline Plus 2T is not recommended for use in any applications where API TC performance oils are required

## Approvals, performance and recommendations

### Performance

- JASO FB (JASO Identification Number: 061CTC567)
- ISO EGB



# Havoline® Plus 2T

Proven performance two-stroke motor cycle oil

continued

## Product specifications

HAVOLINE PLUS 2T KEY PROPERTIES	RESULTS
SAE Grade (J1536)	F/M 2
Product Code	500706
Flash Point, PMCC, °C	124
Pour Point, °C	-19
Sulfated Ash, m %	0.06
Viscosity	
mm <sup>2</sup> /s @ 40°C	67.7
mm <sup>2</sup> /s @ 100°C	9.05

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

**Environment, Health and Safety** Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit [www.caltexoils.com](http://www.caltexoils.com).

For more information, go to [www.chevronlubricants.com](http://www.chevronlubricants.com)