

Delo[®] Gold Ultra

Multifunctional Diesel Engine Oil



Product description

High performance, multigrade, heavy-duty diesel engine oil specifically designed to lubricate a wide range of engines requiring API CI-4 or ACEA E7 performance lubricants, including those fitted Selective Catalytic Reduction (SCR) and / or Exhaust Gas Recirculation (EGR) emission control technologies.

Formulated with ISOSYN[®] technology to provide exceptional soot dispersancy, deposit control and wear protection.

Customer benefits and product features

Customer benefits

Reduces maintenance costs

ISOSYN[®] technology, including a combination of high performance hydrocracked base fluids and carefully balanced metallic detergent and ashless dispersant additive system, helps provide excellent overall engine cleanliness in all service conditions. ISOSYN[®] technology also confers the high degree of soot dispersancy required to maintain oil drain intervals in modern engine designs. Highly effective oxidation stability helps protect against the formation of gums and varnish at elevated temperatures.

Prolongs engine life

High efficiency dispersant combination plus proven metallo-organic anti-wear additive system helps provide excellent protection against wear of critically loaded components under all operating conditions. Multigrade viscosity helps provide additional protection against wear at start-up and under high temperature operating conditions.

Preserves full power and performance

Outstanding metallic detergent additive system helps preserve full power and performance by providing excellent upper-ring-belt deposit control under the high temperatures encountered in turbocharged diesel engines.

Extends oil and filter service intervals

Highly effective antioxidant system inhibits the formation of sludge forming materials which can lead to premature oil thickening and filter plugging. Very effective dispersant system further assists by keeping insoluble contaminants finely suspended in the oil, minimizing their ability to block oil filters.

Applications

- Mixed fleets of diesel engines (high speed, four-stroke, turbocharged or naturally aspirated)
- Four-stroke gasoline engines in mixed fleets of diesel and gasoline engines
- Commercial road transport
- Off-highway vehicles and plant
- Agricultural tractors and farm machinery
- High speed diesel engines in marine service (e.g., fishing boat, river transport)
- Generator sets
- Mobile hydraulic systems (where oil type and viscosity are appropriate)
- Diesel engines utilizing diesel fuels with up to 35% biodiesel (B35)*

*Note: * Based on actual field trial data. When using Biodiesel blended fuel meeting ASTM D7467 (B6 – B20) or equivalent and higher blends when blended with B100 as per ASTM D6751 or equivalent. When using >B6 biodiesel it is critical to monitor the engine oil level and performance. Refer OEM recommendation for oil selection and drain intervals when using biodiesel.*

Delo[®] Gold Ultra

Multifunctional Diesel Engine Oil



Product approvals, performance, and recommendations

Performance standards

- API CI-4, CH-4 / SL
- ACEA E7
- Cummins CES 20078, 77, 76
- Daimler MB-Approval 228.3
- Detroit Diesel 93K215
- Mack EO-N
- MTU Category 2
- Renault RLD-2
- Volvo VDS-3

Meets the Requirements of:

- API CF-4, CF, CD
- ACEA E5-02
- Caterpillar ECF-1-a
- Cummins CES 20072, 20071
- Deutz DQC-III-10
- MAN M 3275-1
- Mack EO-M Plus
- JASO DH-1
- Global DHD-1

Service Considerations

For vehicles fitted with Diesel Particulate Filters (DPF), Delo 400 MGX SAE 15W-40 or Delo 400 SLK SAE 15W-40 should be selected in accordance with the manufacturer's recommendations. The use of these low SAPS (sulfated ash, phosphorus and sulfur) products will maximize intervals between filter cleaning.

While modest by typical heavy duty diesel standards, Delo Gold Ultra has a level of phosphorus higher than permitted by certain recent standards for passenger car motor oils, e.g. ILSAC GF-5, and the ACEA "C" standards. Optimum life of catalytic emission control systems will be achieved by using oils of the performance standard recommended by the vehicle manufacturer.

When using with biodiesel blends containing >6% B100, monitoring oil condition is critical. Fuels with higher biodiesel content increase the risk of fuel dilution in the engine oil. This reduces the oxidation stability of the engine oil as biodiesel tends to oxidise more rapidly thus directly impacting the oil drain intervals. Biodiesel contents greater than B6 have a lower energy content than diesel fuel, which may result in slight horsepower loss and slightly increased fuel consumption.

Always follow OEM recommendation for appropriate fuel and engine oil selection.

This product is not recommended for motorcycle engines.

Delo[®] Gold Ultra

Multifunctional Diesel Engine Oil



Typical Test Data

DELO [®] GOLD ULTRA	TEST METHOD	RESULT
SAE Grade		15W-40
Product Code		500574
Base No., mg KOH/g	ASTM D2896	10.2
Sulfated Ash, m %	ASTM D784	1.4
Kinematic viscosity, mm ² /s @ 40°C mm ² /s @ 100°C	ASTM D445	115
	ASTM D445	15.1
Viscosity Index	ASTM D2270	137

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Delo-Gold-Ultra/PAK/PDSV1_30/10/2023



A Chevron company product

© 2023 Chevron Products Company. Asia Pacific.
All Rights Reserved.