

Clarity[®] Hydraulic Oils AW

Anti-Wear Hydraulic Fluid



Product description

Clarity[®] Hydraulic Oils AW are designed to give excellent protection in mobile and stationary hydraulic vane-, piston-, and gear-type pumps and in high performance industrial applications as well as in environmentally sensitive areas.

Customer benefits and product features

Customer benefits

Premium performance

Ashless formulation meets or exceeds many major vane, piston and gear pump manufacturer's requirements for viscosity, rust and corrosion protection, hydrolytic stability, water separability, foam inhibition, and filterability.

Longer service life

Premium base stocks and additives help provide exceptional oxidation stability and longer service life relative to conventional zinc-based anti-wear hydraulic oils or vegetable hydraulic oils.

Equipment Protection

Excellent anti-wear properties help provide protection for equipment.

Zinc-free/Ashless

Suited for applications involving yellow metals found in piston pumps. Ashless formulation facilitates conventional recycling programs.

Product features

Clarity[®] Hydraulic Oils AW are formulated with premium base oil technology and an ashless ("zinc-free") additive system that provides exceptional oxidation stability, water separability, foam suppression, and protection against wear, rust and corrosion. They are designed to meet or exceed the performance requirements of conventional anti-wear hydraulic oils, especially in severe, high-output applications such as axial piston pumps. The anti-wear performance of these oils makes them especially suited for high performance industrial applications utilizing axial piston pumps, where pressures may exceed 5000 psi. The zinc-free formula makes it well suited for applications involving yellow metals found in hydraulic systems.

Clarity[®] Hydraulic Oils AW

Anti-Wear Hydraulic Fluid



Applications

Clarity[®] Hydraulic Oils AW are designed for use in mobile and stationary hydraulic vane-, piston-, and gear-type pumps.

Clarity[®] Hydraulic Oils AW have shown excellent performance in applications involving servo-valves using multi-metal components.

Clarity[®] Hydraulic Oils AW (ISO 32, 46, 68) are registered by NSF and are acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. The NSF Non-food Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labelling verification.

Clarity[®] Hydraulic Oils AW are not compatible with zinc/calcium containing fluids, and OEM recommended lubricant change-out procedures including drain and flush requirements need to be adhered to.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Product approvals, performance, and recommendations

Performance standards

Clarity[®] Hydraulic Oils AW are developed independently by Chevron to meet the requirements of the following performance standards:

- ASTM D6158 HM (ISO 32, 46, 68)
- ASTM D6158 HV (ISO 100)
- Denison HF-0, HF-2 testing requirements of T5D (ISO 32, 46, 68)
- DIN 51502:1990, HLP fluid (ISO 32, 46, 68)
- DIN 51502:1990, HVLP fluid (ISO 100)
- DIN 51524 (2006-04) Part 2, HLP (ISO 32, 46, 68)
- DIN 51524 (2006-04) Part 3, HVLP (ISO 100)
- Eaton-Vickers for use in M-2950-S (mobile) and I-286-S (stationary) hydraulic systems. Passes Eaton-Vickers 35VQ25 pump test. (ISO 32, 46, 68)
- ISO 6743:1999 Part 4, HM fluid (ISO 32, 46, 68)
- ISO 6743: 1999 Part 4, HV fluid (ISO 100)
- ISO 11158:2009, HM (ISO 32, 46, 68)
- ISO 11158:2009, HV (ISO 100)
- MAG Cincinnati, Cincinnati Machine P68 (ISO 32), P70 (ISO 46), P69 (ISO 68)

Consult OEM representatives for independent verification, updates and recommendations.

Clarity[®] Hydraulic Oils AW

Anti-Wear Hydraulic Fluid



Typical Test Data

CLARITY [®] HYDRAULIC OILS AW	RESULT			
ISO Grade	32	46	68	100
Product Code	520266	520267	520268	520269
Flash Point, COC, °C	222	224	224	226
Pour Point, °C	-33	-30	-30	-40
Viscosity (typical),				
mm ² /s @ 40°C	33.6	46.0	64.6	95.0
mm ² /s @ 100°C	5.6	6.8	8.5	13.8
Viscosity Index (min)	104	101	102	145

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

Visit [Product Information Center](#) >

GEN/Asia Pacific/CHV/PDSv1_07/2007



A Chevron company product

© 2023 Chevron Products Company. Asia-Pacific.
All Rights Reserved.