



Havoline® Manual Transmission Fluid

Manual Transmission Fluid

Product Data Sheet

Customer benefits

- **Maximizes transmission life**
Mild extreme pressure additives provide the load carrying capacity necessary to minimize wear of transmission components under all service conditions.
- **Easy gear selection**
Special combination of friction modifiers, additives and viscosity produce correct frictional characteristics, allowing synchronizer rings and cones to engage properly and enabling light and easy gear shifting and unsurpassed noise control.
- **Saves on maintenance**
Highly refined base oils and effective oxidation inhibitors impart excellent thermal and oxidation stability, providing superior resistance to the formation of lacquer, deposits and corrosive acid by-products.
- **Long fluid service life**
High oxidation stability resists oil degradation and protects against oil thickening and acidity increase.

Applications

- Japanese and Korean passenger car and light commercial vehicle manual transmissions and transaxles.

Not recommended for use in heavy-duty truck and bus manual transmissions, or in spiral bevel or hypoid drive axles where API GL-4 or GL-5 type gear lubricants are specified.

Performance Standards

- Suitable for use in light-duty manual transmissions and transaxles where SAE 80W-90 viscosity is acceptable
- Meets API GL-4 (self-certified)

Product features:

High performance, multigrade manual transmission fluid (MTF) suitable for use in Asian passenger car manual transmissions and transaxles. It may also be used in other manual transmissions fitted to modern passenger car and light commercial vehicles.

A Chevron company product

All trademarks are property owned by Chevron Intellectual Property LLC.





Product specifications

HAVOLINE MANUAL TRANSMISSION FLUID	
KEY PROPERTIES	RESULTS
SAE Grade	80W-90
Product Code	510115
Pour Point, °C	-35
Shear Stability (KRL)	
Visc @ 100°C after shear	14.3
Viscosity,	
mm ² /s @ 40°C	132
mm ² /s @ 100°C	14.5
Viscosity Index	112

Service Considerations

Most original vehicle manufacturers integrate fluid and hardware design, thereby developing tailor-made lubricants for their transmissions. These fluids are used for factory fill and are often specified for in-warranty protection service throughout the manufacturer dealer networks. Unlike commercial vehicle manufacturers, many passenger vehicle manual transmission fluid (MTF) specifications are not publicly available. This means that the only 'approved' lubricant for that transmission is the factory fill fluid.

Havoline® Manual Transmission Fluid SAE 80W-90 has not been formally evaluated by vehicle or transmission manufacturers. However through comprehensive in-house bench test validation and vehicle fleet testing, it has been shown to provide shift quality performance and durability that is comparable to the manufacturer genuine oils. Viscosity grade requirements vary, with many vehicle manufacturers specifying SAE 75W-based multigrades for temperate conditions. However, some manufacturers, such as Toyota, allow the use of SAE 80W-90 viscosity grades in tropical conditions, and Havoline® Manual Transmission Fluid SAE 80W-90 is intended for such cases. It should always be verified that SAE 80W-90 viscosity is acceptable before applying this product to manual transmissions or transaxles.



Havoline® Manual Transmission Fluid

Manual Transmission Fluid

continued

Although Havoline® Manual Transmission Fluid SAE 80W-90 does meet API GL-4, this is a secondary target and it is nevertheless not designed for nor intended for use in any spiral bevel or hypoid drive axles. It is based upon detergent-zinc type additive technology, and so should not be mixed in service with conventional sulfur-phosphorus type EP gear oils, nor should it be used in any manual transmissions or transaxles for which sulfur-phosphorus based fluids are specified, although such are now in the minority where passenger cars and light commercial vehicles are concerned.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com