



# DELO<sup>®</sup> SYN-TRANS XV

## SAE 75W-80

---

### PRODUCT DESCRIPTION

Delo<sup>®</sup> Syn-Trans XV SAE 75W-80 is a premium full synthetic, heavy duty, automated manual transmission fluid formulated specifically for Volvo iShift and Mack mDrive<sup>®</sup> transmissions.

### CUSTOMER BENEFITS

"Delo. Let's go further.<sup>®</sup>"

Delo Syn-Trans XV SAE 75W-80 delivers exceptional value through:

- **Extended drain capabilities** — Provides extended life service up to 500,000 miles in Volvo and Mack automated manual transmissions.
- **Extreme pressure protection** — Protects against transmission gear scuffing, pitting and adhesive wear even at a lower viscosity level allowing for excellent parts protection.
- **Superb thermal and oxidation stability** — Formulated for high temperature performance and excellent oxidation resistance to protect against sludge, varnish, lacquer and harmful deposit buildup in critical transmission components.
- **High viscosity index and low pour point** — Excellent low temperature performance allowing for rapid circulation of the fluid for easier start up and reduced stress on the transmission components.
- **Wide seal compatibility** — This product is compatible with a wide range of seal elastomers helping to prevent seal deterioration and fluid loss.
- **Excellent shear stability** — Contributes to robust viscosity retention and system protection throughout fluid service life.
- **Fuel economy performance** — Provides fuel economy savings compared to more viscous full synthetic SAE 50 and SAE 75W-90 transmission lubricants to help minimize vehicle operating costs.

- **Warranty Plus Protection** — Bumper-to-bumper warranty protection from the engine to the drivetrain that covers lubricant-related damage to your equipment, including parts and labor.<sup>1</sup> Problem resolution and technical advice from Chevron's lubrication experts.
- **Access to Chevron's lubrication and industry knowledge** — Maximizes the bottom line business results of trucking industry professionals.

### FEATURES

Delo Syn-Trans XV SAE 75W-80 is a premium heavy duty, automated manual transmission fluid engineered to provide excellent fluid shear stability and superb frictional characteristics to promote smooth, easy shifting. The high performance additives allow for excellent resistance to rust and corrosion and are compatible with various types of ferrous and yellow metals.

**ISOSYN**  
TECHNOLOGY<sup>®</sup>

### APPLICATIONS

Delo Syn-Trans XV SAE 75W-80 is recommended for use in heavy duty on-road automated manual transmissions when operating under severe conditions and in extremely cold or hot environments. Delo Syn-Trans XV meets and exceeds the requirements of API Service Categories GL-4. In addition, it is approved against:

- **MAN** 341 Type E4
- **Volvo** 97305, 97307, 97318

These approvals allow the use of Delo Syn-Trans XV SAE 75W-80 at extended drain intervals and for use in top-off applications without loss of manufacturer's warranty for these specific transmissions.

---

<sup>1</sup> See Warranty Plus for details and restrictions.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

16 May 2014  
TTF-28

© 2014 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo, Delo. Let's go further., ISOSYN, and the ISOSYN logo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

## TYPICAL TEST DATA

SAE Grade	75W-80
<i>Product Number</i>	223080
<i>SDS Number</i>	35726
API Gravity	35.6
Viscosity, Kinematic cSt at 40°C cSt at 100°C	54.1 9.17
Viscosity, Brookfield cP at -26°C cP at -40°C	3,670 19,300
Viscosity Index	151
Flash Point, °C(°F)	244(471)
Pour Point, °C(°F)	-54(-65)

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.