



Ursa[®] Heavy Duty

SAE 15W-40 and SAE 20W-50

Multigrade heavy-duty diesel oils

Product description

Ursa Heavy Duty SAE 15W-40 and SAE 20W-50 are heavy-duty multigrade engine oils, formulated to conform to ACEA, API and original equipment manufacturers performance standards for heavy-duty diesel engines.

Ursa Heavy Duty multigrades are formulated with premium quality base oils and with a proven additive package, offering robust and reliable performance and protection.

Customer benefits

- Promotes low temperature sludge resistance and high temperature oxidation and piston deposit formation protection
- Detergency performance and acid control help maintain reliability, preventing engine and bearing corrosion and downtime
- Robust wear and bore polishing protection offer extended engine service life

Product highlights

- **Promotes sludge and piston deposit resistance**
- **Offers engine and bearing corrosion protection**
- **Formulated to resist bore polishing**

Selected specification standards include:

ACEA	API
Mack	MAN
Mercedes Benz	MTU
Volvo	

Applications

- Ursa Heavy Duty multigrades are developed for use in heavy duty engine operations, in both on and off highway service. They are designed for turbocharged and naturally aspirated diesel engines in various types of service including engines used in heavy-duty trucks, construction, mining and farming equipment
- Ursa Heavy Duty SAE 15W-40 can also be used in mixed fleet (gasoline and diesel) engines
- Ursa Heavy Duty SAE 15W-40 and SAE 20W-50 also provide protection in engines where oils are recommended meeting the former CCMC D4, PD2 and G4

Approvals, performance and recommendations

Approvals

- MAN M3275-1
- Mercedes Benz MB-Approval 228.3
MB-Approval 229.1
- MTU Category 2 (SAE 15W-40)

Performance

- API CG4/SJ
- ACEA E2
A3/B3 (SAE 15W-40)

Recommendations

Ursa Heavy Duty SAE 15W-40 is suitable for use in:

- API CF-4, CE, CD, CF
- Mack EO-L
- Volvo VDS

Typical test data			
Test	Test Methods	Results	
		SAE 15W-40	SAE 20W-50
Viscosity Grade			
Shelf Life: 60 months from date of filling indicated on the product label			
Density at 15°C, kg/l	ASTM D4052	0.872	0.893
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	105.3	158.5
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	14.7	19.2
Viscosity Index	ASTM D2270	144	138
Pour point, °C	ASTM D5950	-31	-36
Flash point COC, °C	ASTM D92	230	238
Sulphated Ash, %wt	ASTM D874	1.3	1.3

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product