

Delo[®] Gear EP-4

Mild Extreme Pressure Automotive Gear Oil



Product description

Delo[®] Gear EP-4 are multipurpose lubricants. They are made from paraffinic base stocks and contain a carefully balanced additive package to provide gear protection and long lubricant life.

Customer benefits and product features

Customer benefits

Corrosion Delo Gear EP-4 delivers value through:

- **Long gear life**
Extreme pressure properties protect hypoid and other types of gears from scuffing and wear.
- **Rust and corrosion protection**
Effective inhibitor package protects against rusting or corrosion of gear and bearing surfaces.
- **Excellent foam inhibition**
Foaming minimized by use of foam inhibitor.
- **Long lubricant life**
Outstanding thermal and oxidation stability allow high temperature operation with long lubricant life.
- **Seal Protection**
Formulated to protect against oil seal deterioration.

Product features

- The sulfur-phosphorus extreme pressure additive technology used in Delo Gear EP-4 provides exceptional thermal and oxidation stability. In addition, this lubricant is fortified with rust and corrosion inhibitors, a foam inhibitor, and a pour point depressant
- Delo Gear EP-4 minimizes the spalling and wear of gears by creating a microthin sacrificial film on the surface of the gear teeth which is actually softer than the gears themselves. Frictional heat and pressures between gear teeth cause the sulfur-phosphorus to react with the surfaces of the gear teeth at the point of contact, thus creating the sacrificial film. The highly refined base stocks and various inhibitors in the additive package help assure a well-balanced lubricant and long gear and bearing life.

Delo[®] Gear EP-4

Mild Extreme Pressure Automotive Gear Oil



Applications

Delo Gear EP-4 are recommended for use in spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings.

Approvals, performance and recommendations

Delo Gear EP-4 meet the requirements of:

- **API Service Categories** GL-4

Typical Test Data

DELO [®] GEAR EP-4		
SAE Grade	90	140
Product Code	510409	510410
Pour Point, °C	-21	-15
Flash Point, °C	180	180
Viscosity, mm ² /s @ 40°C	190	359
mm ² /s @ 100°C	17.5	26.0
Viscosity Index	99	96

1602

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

Visit [Product Information Center](#) >

Delo Gear EP-4/Asia Pacific/CHV/PDSv1_04/2024



A Chevron company product

© 2024 Chevron Products Company. Asia-Pacific.
All Rights Reserved