

Delo® Starplex Moly 5% EP 2



Product description

Delo® Starplex Moly 5% EP 2 is a premium, multipurpose EP grease.

Customer benefits and product features

Customer benefits

Protects metal surfaces

- Effective EP additive, high base fluid viscosity and additional molybdenum disulfide solid film lubricant protect against component wear under severe conditions and shock loading. Rust and corrosion inhibitors protect metal surfaces, even in conditions of severe water exposure.

Minimizes downtime

- High dropping point minimizes leakage from bearings at elevated temperatures, and excellent oxidation resistance ensures long grease life. Natural water resistance of the lithium complex thickener, tackiness additive, and the additional molybdenum di- sulfide solid film lubricant prevent lubricant failure, even under the wettest conditions.

Ease of application

- Good pumpability characteristics of the lithium complex thickener provide suitable flow properties for most centralized lubrication system applications.

Reduces complexity

- Multipurpose capability allows use in a wide range of automotive and industrial applications, reducing the number of different greases required and eliminating product misapplication.

Product features

- **Delo® Starplex Moly 5% EP 2** contains a ISO 460 base oil, lithium complex thickener, extreme pressure additives, rust and oxidation inhibitors, tackiness additives, and 5% molybdenum disulfide.

Delo® Starplex Moly 5% EP 2



Applications

Can include;

- Heavily loaded pin and bush bearings.
- Mining equipment, such as haul trucks, shovels, excavators, loaders, bulldozers, scrapers and graders.
- Backhoes and shovels.
- Road rollers.
- Agricultural tractors, combines and cotton pickers.
- Construction equipment, such as bulldozers, scrapers, earthmovers and cranes.
- Heavy-duty transport.

Usable temperature range in continuous service is -20 to 130°C. Maximum temperature for short term exposure is 210°C.

Product approvals, performance and recommendations

Performance standards

- ISO 6743-9 ISO-L-XBDEB 2
- DIN 51502 KPF2K-20

Meets the requirements of the following OEM specifications:

- Caterpillar Multipurpose Molybdenum Grease (MPGM) Specification containing 5% molybdenum disulfide (Extreme Application Grease NLGI 2)
- Bucyrus SD 4711 MPG - multipurpose grease specifications
- Komatsu Mining Germany Works Standard

Service considerations

The inclusion of molybdenum disulfide provides an extra measure of protection under shock loading which is very common in construction, off-highway transport, and agricultural usage. During heavy shock loading, the lubricant film between metal surfaces can be temporarily ruptured or squeezed out. When using Delo® Starplex Moly 5% EP 2, some molybdenum disulfide stays in place as a solid film lubricant to protect metal surfaces, even under extreme shock loading conditions, preventing metal-to-metal contact which could cause component damage. The presence of molybdenum disulfide is also valuable in dirty environments, or when proper re-greasing intervals cannot be followed.

Delo® Starplex Moly 5% EP 2 is not recommended for constant-velocity joints on front wheel drive vehicles.

Delo[®] Starplex Moly 5% EP 2



Typical test data

DELO [®] STARPLEX MOLY 5% EP 2		
TEST METHOD		RESULTS
NLGI Grade		2
Product Code		510868
Dropping Point, °C	ASTM D2265	230+
Four Ball Weld Point, kg	ASTM D2596	500
Molybdenum Disulfide, m%		5
Base Oil Blend Viscosity		
mm ² /s @ 40°C	ASTM D445	460
mm ² /s @ 100°C	ASTM D445	30.7
Penetration, Worked @ 25°C	ASTM D217	280
Timken OK Load, kg	ASTM D2509	>25

1901

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center

[Visit Product Information Center >](#)

Delo[®] Starplex Moly 5% EP2/Asia Pacific/CHV/PDSv1_03/2024



A Chevron company product
© 2024 Chevron Products Company. Asia Pacific.
All Rights Reserved.