



Customer benefits

Protects equipment

Proven performance fibrous sodium soap greases with high viscosity base oil and stickiness offers reliable film strength and good surface adhesion. The fibrous content offers protection from contaminants such as dust and dirt by helping provide a reliable seal.

Good service life

Marfak greases have a sodium component, designed to provide inherent rust protection capability, by emulsifying small amounts of water.

Applications

Can include:

- Use as chassis lubricants for passenger cars, trucks, buses, farm and construction equipment
- Centralized lubrication systems

Usable temperature range in continuous service is:

-20 to 95°C

Product features:

- **Marfak® 00** is a general purpose long-fiber viscous and sticky grease containing a high viscosity mineral base oil and a sodium soap thickener for use in general purpose automotive and industrial applications. It provides a tough, durable lubricating film that resists squeezing out and provides good rust protection

Typical key properties

MARFAK® 00		
NLGI Grade		00
Product Code		510800
	TEST METHOD	
Dropping Point, °C	ASTM D 2265	N/A
Base Oil Viscosity,		
- mm ² /s @ 40°C	ASTM D 445	1100
- mm ² /s @ 100°C	ASTM D 445	>45.5
Penetration worked, 60x, mm/10		400-430
Thickener type		Sodium
Thickener, %	ASTM D 0128	3.5
Emcor corrosion test	IP 220	0/0

1605

Performance standards

- DIN 51502 G00H-20
- ISO 6743-09 ISO-L-XBBAA 00

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.chevronlubricants.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
 – Asia Pacific