



CLARITY[®] HYDRAULIC OIL AW ISOCLEAN[®] CERTIFIED LUBRICANT 32, 46, 68

PRODUCT DESCRIPTION

Clarity[®] Hydraulic Oils AW ISOCLEAN[®] Certified Lubricants are designed with ashless technology to give excellent protection in mobile and stationary hydraulic vane-, piston-, and gear-type pumps in high-performance industrial applications, as well as in environmentally sensitive areas. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



- **Exceptional oxidation stability** — Longer service life than conventional zinc-based antiwear hydraulic oils or vegetable hydraulic oils.
- **Excellent antiwear properties** — Provides excellent wear protection.
- **Low toxicity** — Inherently biodegradable¹ and has very low acute aquatic toxicity to both fish and invertebrates based on tests of water accommodated fractions. Ashless formulation facilitates conventional recycling programs.
- **Zinc-free/Ashless** — Suited for applications involving yellow metals found in pumps.

CUSTOMER BENEFITS

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants deliver value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Premium performance** — Ashless formulation meets or exceeds major vane, piston and gear pump manufacturer's requirements for viscosity, rust and corrosion protection, hydrolytic stability, water separability, foam inhibition, and filterability.

FEATURES

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are formulated with premium base oil technology and an ashless ("zinc-free") additive system that provides exceptional oxidation stability, water separability, foam suppression, and protection against wear, rust and corrosion. They are designed to meet or exceed the performance requirements of conventional antiwear hydraulic oils, especially in severe, high-output applications such as axial piston pumps. The antiwear performance of these oils makes them especially suited for high performance industrial applications where pressures may exceed 5000 psi.



1. As determined by OECD 301D (Closed Bottle Biodegradability Test), Chevron Clarity Hydraulic Oil AW was shown to be inherently biodegradable. This test is normally run for 28 days. After completing this test period, Chevron Clarity Hydraulic Oil AW was 38% degraded. Degradation of 20-59% after 28 days in OECD 301D is evidence that a product is inherently biodegradable. Chevron Clarity Hydraulic Oil AW did not meet the criteria for readily biodegradable, which is degradation of $\geq 60\%$ after 28 days in OECD 301D.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

10 October 2020
IO-25 ISOCLEAN

© 2009-2020 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Clarity and ISOCLEAN are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

The zinc-free formula makes it well suited for applications involving yellow metals found in hydraulic systems.

Clarity® Hydraulic Oils AW ISOCLEAN® Certified Lubricants are long-life lubricants (are not vegetable oil based), with dramatically longer TOST (ASTM D943 oxidation stability test) lives than conventional zinc-based hydraulic fluids. A longer TOST life equates to longer service life, which can improve the customer's bottom line. This level of oxidation stability is especially applicable in high efficiency (high speed, high temperature, high output) applications where severe stress is placed on the hydraulic fluid.

Clarity Hydraulic Oil AW 100 is a shear-stable high VI hydraulic oil designed to improve equipment efficiency and increase operating temperature range of this grade.

Many hydraulic systems are required to operate in environmentally sensitive areas where leaks or spills of hydraulic fluid may result in contamination of the soil or nearby waterways. Conventional antiwear hydraulic oils are formulated with metal-containing performance additives which can persist in the environment in the event of leaks. Vegetable-based hydraulic oils generally meet the environmental requirements, but can fall short of the performance requirements.

APPLICATIONS

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are designed for and have shown excellent performance in applications involving:

ISO Grade	32	46	68
high performance industrial applications where pressures may exceed 5000 psi	X	X	X
lightly loaded reciprocating compressors	X	X	X

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are not compatible with zinc/calcium containing fluids, and OEM recommended lubricant change-out procedures including drain and flush requirements need to be adhered to.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

CLAIMS AND SPECIFICATIONS

ISO Grade	32	46	68
Blohm+Voss	M	M	M
Eaton (Vickers) 35VQ25A (Pump Test) I-286-S (Stationary) M-2950-S (Mobile)	M	M	M
Fives Cincinnati (formerly MAG ^a Cincinnati, Cincinnati Machine, Cincinnati Milacron)	M p-68	M p-70	M p-69
Hitachi/John Deere Construction JCMAS HK VG 32, 46	M	M	
Krauss-Maffei Kunststofftechnik		M	
NSF H2 ^b	A	A	A
Parker Hannifin (Denison) HF-0, HF-1, HF-2, T6H20C	M	M	M
Voith 3625-006058	A	A	A
ZF TE-ML 04K	M	M	
ASTM D6158 HM	M	M	M
DIN 51524-2 HLP	M	M	M
ISO 11158 L-HM	M	M	M

a Obsolete specification

b Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants (ISO 32, 46, 68) are registered by **NSF** and are acceptable as lubricants where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.

A: Approved for

M: Meets or exceeds requirements

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

ISO Grade	Test Method	32	46	68
Product Number		278024	278023	278022
SDS Number U.S. Mexico Colombia		6691 6691MEX 32531	6691 6691MEX 32531	6691 6691MEX 32531
API Gravity	ASTM D287	33.3	31.9	31.6
Density at 15°C, kg/L	ASTM D4057	0.8581	0.8654	0.8670
Viscosity, Kinematic cSt at 40°C cSt at 100°C	ASTM D445	33.5 5.6	46.1 6.8	67.8 8.5
Viscosity, Saybolt SUS at 100°F SUS at 210°F	ASTM D2161	155 45.0	237 49.0	334 54.8
Viscosity Index	ASTM D2770	105	101	95
Flash Point, °C(°F)	ASTM D92	222(432)	224(435)	224(435)
Pour Point, °C(°F)	ASTM D97	-38(-36)	-36(-33)	-32(-26)
Copper Corrosion 3h at 100°C	ASTM D130	1b	1b	1b
Foam Test, Seq. I Tendency, mL Stability, mL	ASTM D892	10 0	20 0	50 0
Rust Test, Procedure A & B	ASTM D665	Pass	Pass	Pass
Water Separability, minutes to <3mL at 54°C	ASTM D1401	10	10	10
Water Separability, minutes to <3mL at 82°C	ASTM D1401	—	—	—
Oxidation Stability, TOST Hours to 2.0 mg KOH/g acid number	ASTM D943 ^a	> 10,000	> 10,000	> 10,000
FZG Gear Test, Fail Load Stage	DIN 51354	12	≥12	≥12
Acute Aquatic Toxicity (LC-50)	OECD 203	Pass	Pass	Pass

a Modified ASTM D943, allowed to run beyond 10,000 h.

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.