



CLARITY[®] HYDRAULIC OIL AW ISOCLEAN[®] CERTIFIED LUBRICANT 32, 46, 68

PRODUCT DESCRIPTION

Clarity[®] Hydraulic Oils AW ISOCLEAN[®] Certified Lubricants are designed to give excellent protection in mobile and stationary hydraulic vane-, piston-, and gear-type pumps and in high-performance industrial applications as well as in environmentally sensitive areas. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



- **Exceptional oxidation stability** — Longer service life than conventional zinc-based antiwear hydraulic oils or vegetable hydraulic oils.
- **Excellent antiwear properties** — Provides excellent wear protection.
- **Low toxicity** — Inherently biodegradable¹ and has very low acute aquatic toxicity to both fish and invertebrates based on tests of water accommodated fractions. Ashless formulation facilitates conventional recycling programs.
- **Zinc-free/Ashless** — Suited for applications involving yellow metals found in piston pumps.

CUSTOMER BENEFITS

Clarity Hydraulic Oil AW ISOCLEAN Certified Lubricants deliver value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Premium performance** — Ashless formulation meets or exceeds major vane, piston and gear pump manufacturer's requirements for viscosity, rust and corrosion protection, hydrolytic stability, water separability, foam inhibition, and filterability.

FEATURES

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are formulated with premium base oil technology and an ashless ("zinc-free") additive system that provides exceptional oxidation stability, water separability, foam suppression, and protection against wear, rust and corrosion. They are designed to meet or exceed the performance requirements of conventional antiwear hydraulic oils, especially in severe, high-output applications such as axial piston pumps. The antiwear performance of these oils makes them especially suited for high performance industrial applications utilizing axial piston pumps where pressures may exceed 5000 psi.



1. As determined by OECD 301D (Closed Bottle Biodegradability Test), Chevron Clarity Hydraulic Oil AW was shown to be inherently biodegradable. This test is normally run for 28 days. After completing this test period, Chevron Clarity Hydraulic Oil AW was 38% degraded. Degradation of 20-59% after 28 days in OECD 301D is evidence that a product is inherently biodegradable. Chevron Clarity Hydraulic Oil AW did not meet the criteria for readily biodegradable, which is degradation of $\geq 60\%$ after 28 days in OECD 301D.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

29 July 2016
IO-25 ISOCLEAN

© 2009-2016 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Clarity and ISOCLEAN are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

The zinc-free formula makes it well suited for applications involving yellow metals found in hydraulic systems.

Clarity® Hydraulic Oils AW ISOCLEAN® Certified Lubricants are long-life lubricants (are not vegetable oil based), with dramatically longer TOST (ASTM D943 oxidation stability test) lives than conventional zinc-based hydraulic fluids. A longer TOST life equates to longer service life, which can improve the customer's bottom line. This level of oxidation stability is especially applicable in high efficiency (high speed, high temperature, high output) applications where severe stress is placed on the hydraulic fluid.

Many hydraulic systems are required to operate in environmentally sensitive areas where leaks or spills of hydraulic fluid may result in contamination of the soil or nearby waterways. Conventional antiwear hydraulic oils are formulated with metal-containing performance additives which can persist in the environment in the event of leaks. Vegetable-based hydraulic oils generally meet the environmental requirements, but can fall short of the performance requirements.

APPLICATIONS

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are designed for use in mobile and stationary hydraulic vane-, piston-, and gear-type pumps.

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants have shown excellent performance in applications involving servo-valves using multimetal components.

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants meet the requirements of:

- **ASTM D6158 HM** (ISO 32, 46, 68)
- **Denison** HF-0, HF-2 testing requirements of T5D (ISO 32, 46, 68)
- **DIN** 51524-2 (ISO 32, 46, 68)
- **Eaton-Vickers** for use in M-2950-S (mobile) and I-286-S (stationary) hydraulic systems. Passes Eaton-Vickers 35VQ25 pump test. (ISO 32, 46, 68)
- **ISO 11158 L-HV** (ISO 22, 100)
- **Fives Cincinnati** (formerly MAG Cincinnati, Cin Machine, Cin Milacron) P-68 (ISO 32), P-70 (ISO 46), P-69 (ISO 68)

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are registered by **NSF** and are acceptable

as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.

Clarity Hydraulic Oils AW ISOCLEAN Certified Lubricants are not compatible with zinc/calcium containing fluids, and OEM recommended lubricant change-out procedures including drain and flush requirements need to be adhered to.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Consult with your Chevron Lubricant Representative or Chevron ISOCLEAN Certified Lubricants Marketer to set specific ISO Cleanliness targets for your business application.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

ISO Grade	32	46	68
<i>Product Number</i>	278024	278023	278022
<i>SDS Number</i>	6691	6691	6691
API Gravity	32.8	31.9	31.8
Viscosity, Kinematic cSt at 40°C cSt at 100°C	33.6 5.6	46.0 6.8	64.6 8.5
Viscosity, Saybolt SUS at 100°F SUS at 210°F	173 45.0	237 49.0	334 54.8
Viscosity Index	104	101	102
Flash Point, °C(°F)	222(432)	224(435)	224(435)
Pour Point, °C(°F)	-33(-27)	-30(-22)	-30(-22)
Oxidation Stability Hours to 2.0 mg KOH/g acid number, ASTM D943	> 18,000 ^a	> 18,000 ^a	> 18,000 ^a
FZG Gear Test, DIN 51354, Fail Stage	12	≥12	≥12
Acute Aquatic Toxicity (LC-50, OECD 203)	Pass	Pass	Pass

a Modified ASTM D943, allowed to run beyond 10,000 h.

The test results expressed above were obtained during the development of the product line and are considered representative of any/all commercial samples.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

29 July 2016
IO-25 ISOCLEAN