



# RANDO® HDZ ISOCLEAN® CERTIFIED LUBRICANT

## 15, 22, 32, 46, 68, 100

### PRODUCT DESCRIPTION

Rando® HDZ ISOCLEAN® Certified Lubricants are formulated with premium base oil technology and designed to give robust protection to hydraulic pumps in mobile and stationary systems. These are high viscosity index hydraulic oils that provide a wide operating temperature range. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



- **High viscosity index** — Minimum change in viscosity over a wide range of operating temperatures.
- **Foam inhibition** — Contains special foam suppressant.
- **Excellent antiwear properties** — Provides excellent wear protection.
- **Good stability** — in the presence of water in the ASTM D2619 Hydrolytic Stability Test and in the presence of copper and steel in the MAG Cincinnati Machine Thermal Stability Test.
- **Fast water separation** — Protects against rust problems by fast release of water.
- **Good filterability** — Excellent thermal and hydrolytic stability helps prevent formation of deposits which may interfere with filtration in equipment having close tolerances.

### CUSTOMER BENEFITS

Rando HDZ ISOCLEAN Certified Lubricants deliver value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **High oxidation stability** — Long service life in high pressure service.
- **Protection against rust and corrosion** — Gives excellent protection against corrosion of both copper and steel. Passes the ASTM D665A distilled water rust test and ASTM D665B salt water rust test.

### FEATURES

Rando HDZ ISOCLEAN Certified Lubricants incorporate antiwear additives, oxidation and corrosion inhibitors, foam and aeration suppressants, and a shear stable viscosity index improver.



Hydraulic systems, due to the nature of their operation, experience accelerated wear unless they are protected by clean, high quality antiwear hydraulic oils. Surging pressures in pumps and valves can increase metal-to-metal contact unless antiwear protection is present. The antiwear additives in Rando HDZ ISOCLEAN Certified Lubricants plate out on the metal surfaces. This plating minimizes metal-to-metal contact, which is most severe in vane-, piston-, and gear-type pumps. As hydraulic pressures increase over

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

18 March 2022  
IO-174 ISOCLEAN

© 2008-2022 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, ISOCLEAN and Rando are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

1000 psi, the need for antiwear protection increases proportionally.

In field performance demonstrations, Rando HDZ ISOCLEAN Certified Lubricants provided up to 3.4% improvement in overall hydraulic pump efficiency when compared to a typical conventional hydraulic oil (a lower VI product with VI<105).

**APPLICATIONS**

<b>ISO Grade</b>	<b>15</b>	<b>22</b>	<b>32</b>	<b>46</b>	<b>68</b>	<b>100</b>
high performance industrial applications where pressures may exceed 5000 psi			X	X	X	
lightly loaded reciprocating compressors			X	X	X	
hydraulic equipment reduction gears where EP is not required						X
plain and antifriction bearings						X
circulating oil systems						X
applications where AGMA rust and oxidation inhibited oils are required						X

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

## CLAIMS AND SPECIFICATIONS

ISO Grade	15	22	32	46	68	100
Arburg Injection Molding				A		
Bosch Rexroth RDE 90245			A	A	A	
Bosch Rexroth RA & RE 90220 <sup>a</sup> , 90221 <sup>a</sup>			M	M	M	
Eaton (Vickers) 35VQ25A (Pump Test) I-286-S (Stationary) M-2950-S (Mobile)			M	M	M	
Fives Cincinnati <sup>a</sup> (formerly MAG Cincinnati, Cincinnati Machine, Cincinnati Milacron)			M p-68	M p-70	M p-69	
Frank Mohn, (Framo) hydraulic cargo pumping				A		
MAN Truck & Bus OEM Engine Specifications	A					
Parker Hannifin (Denison) HF-0, HF-1, HF-2			A	A	A	
ZF TE-ML 04R			A	A		
ANSI/AGMA 9005-E02, 9005-F16 R&O			M	M	M	M
ASTM D6158 HM, HV	M	M	M	M	M	M
DIN 51524-2 HLP, 51524-3 HVLP	M	M	M	M	M	M
ISO 11158 L-HM, L-HV	M	M	M	M	M	M
JCMAS HK VG 32, 46			M	M		
SAE MS1004-HM, HV		M	M	M	M	M
US Steel (AIST) 126,127			M	M	M	

<sup>a</sup> Obsolete specification

**A:** Approved for

**M:** Meets or exceeds requirements

Refer to the service manual of the equipment to ensure that the minimum fluid viscosity requirements are met at the highest operating temperature. Please consult with your equipment manufacturer if equipment is operating outside normal operating conditions.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

**TYPICAL TEST DATA**

ISO Grade	Test Method	15	22	32	46	68	100
Product Number		278064	278065	254609	254610	254611	274323
SDS Number							
U.S.		23543	42265	23537	23537	23537	23537
Canada		23544	42266	23538	23538	23538	23538
Mexico		23545	42267	23529	23529	23529	23539
Colombia			51622	51622	51622	51622	51622
API Gravity	ASTM D287	27.4	32.9	34	32.2	30.8	30.4
Density at 15°C, kg/L	ASTM D4057	0.8897	0.8544	0.843	0.8638	0.8706	0.8728
Viscosity, Kinematic							
cSt at 40°C	ASTM D445	15.8	22.6	33.2	47.1	69.6	97.8
cSt at 100°C		3.9	5.1	6.6	8.3	11.2	14.0
Viscosity, Saybolt							
SUS at 100°F	ASTM D2161	81.4	108	150	214	316	464
SUS at 212°F		39.1	43.0	46.9	53.1	62.8	74.8
Viscosity Index	ASTM D2770	148	152	159	155	154	146
Flash Point, °C(°F)	ASTM D92	150(302)	188(370)	220(428)	216(420)	212(414)	232(450)
Pour Point, °C(°F)	ASTM D97	-62(-80)	-54(-65)	-50(-58)	-46(-51)	-43(-45)	-40(-40)
Brookfield Viscosity							
cP at -20°C		500	750	1290	2330	4450	8040
cP at -30°C	ASTM D2983	1660	2340	4900	9120	19300	-
cP at -40°C		6920	9120	25100	-	-	-
Copper Corrosion 3h at 100°C	ASTM D130	1b	1b	1b	1b	1b	1b
Foam Test, Seq. I							
Tendency, mL	ASTM D892	50	40	10	0	0	0
Stability, mL		0	0	0	0	0	0
Rust Test, Procedure A & B	ASTM D665	Pass	Pass	Pass	Pass	Pass	Pass
Water Separability, minutes to <3mL at 54°C	ASTM D1401	10	10	10	15	15	—
Water Separability, minutes to <3mL at 82°C	ASTM D1401	—	—	—	—	—	10
Oxidation Stability, TOST Hours to 2.0 mg KOH/g TAN	ASTM D943	—	—	>5000	>5000	>5000	>3000

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

ISO Grade	Test Method	15	22	32	46	68	100
FZG Gear Test Fail Load Stage	DIN 51354	—	—	12	12	12	12
Dielectric Strength, kV <sup>a</sup>	ASTM D877 <sup>b</sup>	35	35	35	35	35	35

a Dielectric strength value applies only to "point of manufacture" of packaged products produced at a Chevron manufacturing facility. (Does not apply to bulk packaging). The oil will quickly lose its high dielectric strength value when exposed to contamination and to very small amounts of moisture and water.

b Industry standard test method for measuring kV values is not precise and test results can differ significantly.

Minor variations in product typical test data are to be expected in normal manufacturing. In a clean, dry environment, Rando HDZ 15, 22, 32, 46, 68 and 100 typically meet a dielectric strength of 35 kVa (ASTM D877b).

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.