



Havoline® ProDS F SAE 0W-30

Premium performance synthetic passenger car engine oil

Product description

Havoline ProDS F SAE 0W-30 is a premium performance synthetic passenger car engine oil designed for use in recent Ford Focus and Ford Mondeo TDCi diesel engines requiring Ford WSS-M2C950-A.

It is formulated with synthetic base oils in combination with an advanced mid SAPS additive system and is compatible with diesel particulate filter (DPF) and three-way catalyst (TWC) technologies.

Havoline ProDS F SAE 0W-30 is designed to deliver long-life engine wear resistance, cold temperature protection, reduced exhaust emissions, and improved fuel efficiency.

Customer benefits

- Designed to reduce engine friction and provide improved fuel economy without compromising on reliability and durability
- Helps reduce maintenance costs through extended drain periods and engine and emissions system protection
- Designed to minimise emissions through mid SAPS technology and helps protect catalysts and diesel particulate filter systems
- Low temperature fluidity aids rapid lubricant circulation during cold engine starts, contributing to increased engine protection
- Synthetic base oils in combination with advanced cleaning additives minimise deposit formation and wear, helping extend engine life
- Advanced cleaning additives designed to minimise deposit and sludge build-up help extend engine life and maintain fuel economy

Product highlights

- **Designed for improved fuel economy**
- **Offers long-life engine and emission system protection**
- **Helps protect catalysts and diesel particulate filter systems**
- **Low temperature engine protection**
- **Promotes extended engine life**

Selected specification standards include:

ACEA	Ford
Fiat	Jaguar Land Rover

Applications

- Havoline ProDS F SAE 0W-30 is specifically designed for the Ford 2.0L Focus diesel engines manufactured from September 2014 and the Ford 2.0L Mondeo diesel engines manufactured from 2015*.
- Havoline ProDS F SAE 0W-30 is suitable for use in other models such as C-Max, Grand C-Max, Kuga and can also be used for gasoline engines*.
- Havoline ProDS F SAE 0W-30 is not suitable for all engine types.

* Consult owners' manual if in doubt.

Approvals, performance and recommendations

Approvals

- Ford WSS-M2C950A, Acknowledged by Ford Motor Co
- Jaguar Land Rover STJLR.03.5007

Performance

- ACEA C2

Suitable for use

Havoline ProDS F SAE 0W-30 is suitable for use in engines requiring:

- Fiat 9.55535 GS1

Typical test data

Test	Test Methods	Results
Viscosity Grade		SAE 0W-30
Shelf Life: 60 months from date of filling indicated on the product		
Density at 15 °C, kg/l	ASTM D4052	0.841
Kinematic viscosity at 40 °C, mm ² /s	ISO 3104	45
Kinematic viscosity at 100 °C, mm ² /s	ISO 3104	9.4
Viscosity Index	ISO 2909	200
Pour Point, °C	ISO 3016	-52
Flash Point COC, °C	ISO 2592	228

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A Chevron company product