



# Havoline ProDS F 0W-30

## Premium performance synthetic engine oil

### Product description

Havoline® ProDS F 0W-30 is a premium performance synthetic engine oil, especially designed for use in Ford TDCi diesel engines requiring Ford WSS-M2C950-A.

Havoline ProDS F 0W-30 is formulated with synthetic base oils and advanced additives, designed for durability, wear protection, low temperature performance, reduced exhaust emissions, and fuel efficiency. It is a mid SAPS oil compatible with diesel particulate filters (DPF) and three-way catalysts (TWC).

### Customer benefits

- Reduces internal friction and provides enhanced fuel economy without compromising on durability.
- Helps minimize off road time throughout extended drain thanks to advanced engine protection and emission system protection.
- Helps minimize exhaust emissions – through mid SAPS technology designed to protect catalysts and diesel particulate filter systems.
- Low temperature fluidity aids rapid lubricant circulation during cold engine starts, contributing to increased engine protection.
- Use of synthetic base oils in combination with advanced cleaning additives helps minimize deposit formation and wear extending engine life.
- Contains advanced cleaning additives designed to help minimize deposit and sludge build-up extending engine life while maintaining fuel economy.

### Product highlights

- **Formulated for enhanced fuel economy and extended engine life**
- **Helps to optimise on-road time**
- **Designed for TWC and DPF protection**
- **Cold-start protection**
- **Aids deposit formation resistance**
- **Helps maintain fuel economy**

#### Selected specification standards include:

ACEA	Ford
Fiat	Jaguar Land Rover
Volkswagen	

## Applications

- Havoline ProDS F SAE 0W-30 is specifically designed for many Ford diesel engines manufactured from September 2014 onwards. This oil can also be used for some gasoline engines.

Havoline ProDS F SAE 0W-30 is not suitable for all engine types

\*Consult owner manual if in doubt.

## Approvals, performance and suitable for use

### Approvals

- Ford WSS-M2C950A  
(Acknowledged by Ford Motor Co)
- Jaguar Land Rover STJLR.03.5007

### Performance

- ACEA C2
- Volkswagen VWC 53035

### Suitable for use

Havoline ProDS F SAE 0W-30 is suitable for use in engines requiring:

- Fiat 9.55535 GS1

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 0W-30
<b>Shelf Life: 60 months from date of filling indicated on the product</b>		
Density at 15 °C, kg/l	ASTM D4052	0.841
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	45
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	9.4
Viscosity Index	ASTM D2270	200
Pour Point, °C	ASTM D97	-52
Flash Point COC, °C	ASTM D92	228

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

**Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.**

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see [www.texacolubricants.com](http://www.texacolubricants.com).

A **Chevron** company product