



# Havoline® ProDS F SAE 0W-30

## Premium performance synthetic passenger car engine oil

### Product description

Havoline ProDS F SAE 0W-30 is a premium performance synthetic passenger car engine oil designed for use in recent Ford Focus and Ford Mondeo TDCi diesel engines requiring Ford WSS-M2C950-A.

It is formulated with synthetic base oils in combination with an advanced low SAPS additive system and is compatible with diesel particulate filter (DPF) and three-way catalyst (TWC) technologies.

Havoline ProDS F SAE 0W-30 is designed to deliver long-life engine wear resistance, cold temperature protection, reduced exhaust emissions, and improved fuel efficiency.

### Customer benefits

- Designed to reduce engine friction and provide improved fuel economy without compromising on reliability and durability
- Helps reduce maintenance costs through extended drain periods and engine and emissions system protection
- Designed to minimise emissions through low SAPS technology and helps protect catalysts and diesel particulate filter systems
- Low temperature fluidity aids rapid lubricant circulation during cold engine starts, contributing to increased engine protection
- Synthetic base oils in combination with advanced cleaning additives minimise deposit formation and wear, helping extend engine life
- Advanced cleaning additives designed to minimise deposit and sludge build-up help extend engine life and maintain fuel economy

### Product highlights

- **Designed for improved fuel economy**
- **Offers long-life engine and emission system protection**
- **Helps protect catalysts and diesel particulate filter systems**
- **Low temperature engine protection**
- **Promotes extended engine life**

#### Selected specification standards include:

ACEA	Ford
Jaguar Land Rover	

## Applications

- Havoline ProDS F SAE 0W-30 is specifically designed for the Ford 2.0L Focus diesel engines manufactured from September 2014 and the Ford 2.0L Mondeo diesel engines manufactured from 2015\*.
- Havoline ProDS F SAE 0W-30 is suitable for use in other models such as C-Max, Grand C-Max, Kuga and can also be used for gasoline engines\*.
- Havoline ProDS F SAE 0W-30 is not suitable for all engine types.

\* Consult owners' manual if in doubt.

## Approvals, performance and recommendations

### Performance

- ACEA C2
- Ford WSS-M2C950-A
- Jaguar Land Rover STJLR.03.5007

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 0W-30
<b>Shelf Life: 60 months from date of filling indicated on the product</b>		
Density at 15 °C, kg/l	ASTM D4052	0.841
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ISO 3104	44.2
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ISO 3104	9.3
Viscosity Index	ISO 2909	205
Pour Point, °C	ISO 3016	-52
Flash Point COC, °C	ISO 2592	220

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

**Disclaimer** Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

**Health, safety, storage and environmental** Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

**A Chevron company product**