

Havoline® Synthetic Blend SAE 5W-30

Passenger Car Motor Oil



Product description

Havoline® Synthetic Blend SAE 5W-30 with Deposit Shield™ Technology, has specific tailored viscosity characteristics and effective friction modifier that provides outstanding protection and delivers fuel economy performance. Its advanced formulation provides turbocharger protection and protection against occurrence of low speed pre-ignition.

Customer benefits and product features

Customer benefits

- **Outstanding protection against Low Speed Pre Ignition (LSPI) events**
Specially formulated to protect against LSPI occurrence in turbocharged and/or newer gasoline direct-injection vehicles, which over time reduces engine damage.
- **Maintains high power and performance**
Proven metallo-organic anti-wear additive system protects engines under all operating conditions by providing excellent wear control in even the most sophisticated valve train mechanisms, including those with variable valve timing. Works immediately upon contact to create a protective coating that shields the engine against deposits that lead to loss of performance. Provides excellent control of piston and ring deposits under high temperature conditions.
- **Increase engine durability, prolonged engine life**
Deposit Shield™ Technology delivers high thermal stability, excellent oxidation resistance, providing outstanding wear protection on vital engine parts, increasing engine durability.
- **Delivers fuel economy performance**
Specially tailored viscosity characteristics and effective friction modifier minimizes internal engine frictional losses for maximum fuel economy.

Product features

- Havoline Synthetic Blend SAE 5W-30 is a resource conserving, multi-grade gasoline engine oil for use in passenger cars and light truck engines requiring low viscosity, ILSAC GF-6 or API SP performance lubricants.

Havoline® Synthetic Blend SAE 5W-30

Passenger Car Motor Oil



Applications

- Naturally aspirated and turbocharged gasoline direct injection engines in passenger cars where ILSAC GF-6, API SP, or earlier ILSAC or API "S" performance categories are specified.
- Light truck gasoline engines where ILSAC GF-6, API SP, or earlier ILSAC or API "S" performance categories are specified.
- Passenger car and light truck spark ignition engines burning gasoline/ethanol blends up to and including E85.
- Small displacement turbo-charged engines especially those requiring low speed pre-ignition (LSPI) protection.

Not recommended for use in diesel engines, motorcycle engines, or gasoline engines that require ACEA classified oils.

Approvals, performance and recommendations

Performance standards

- ILSAC GF-A
- API SP and Resource Conserving (Licensed)

Havoline® Synthetic Blend SAE 5W-30

Passenger Car Motor Oil



Typical test data

HAVOLINE® SYNTHETIC BLEND	RESULT
SAE Grade	5W-30
Product Code	500201
Base no. (D2896, mg KOH/g)	7.0
Phosphorous, m%	0.07
Ash, Sulfated, m%	0.7
Viscosity, mm ² /s @ 100°C	10.1
Viscosity Index	152
Zinc, m%	0.08

2310

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Havoline® Synthetic Blend 5W-30/MEA/CHV/PDSv1_04/2024



Chevron company product

© 2024 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.