



Havoline[®] ProDS Full Synthetic Motor Oil SAE 5W-30

Premium performance synthetic engine oil

Product description

Havoline ProDS Full Synthetic Motor Oil SAE 5W-30 is a premium performance full synthetic, extended drain engine oil designed for arduous, high temperature stop-start city driving, combined with low temperature fluidity that helps to ensure rapid protection in cold engine starts.

Havoline ProDS Full Synthetic Motor Oil SAE 5W-30 offers proven improved fuel economy and protects against corrosion and piston varnish in high temperature conditions in turbocharged engines and those working under heavy loads.

Customer benefits

- Advanced additive technology designed to protect against corrosion and piston varnish in high temperature driving conditions
- Proven fuel economy performance shown in industry-standard testing
- Premium additive technologies offer protection against component wear in cold engine start-ups
- Proven in latest industry testing to prevent engine super-knock caused by Low Speed Pre-Ignition (LSPI)
- Powerful keep-clean technology offers protection against deposits and sludge build-up, helping maintain fuel economy
- Designed to reduce oil consumption with advanced synthetic formulation offering long-life, low volatility performance

Product highlights

- **Designed to protect in high temperature conditions**
- **Proven fuel economy performance**
- **Offers protection at cold engine start-up**
- **Proven Low Speed Pre-Ignition resistance**
- **Promotes keep-clean engine protection**
- **Formulated for long, low volatility service**

Selected specification standards include:

API	Chrysler
Fiat	Ford
GM	Honda
ILSAC	

Applications

- Havoline ProDS Full Synthetic Motor Oil SAE 5W-30 is suitable for Acura, Chrysler, FCA, Ford, GM, Honda, Mazda, Nissan and Toyota engines requiring this grade of engine oil

Havoline ProDS Full Synthetic Motor Oil SAE 5W-30 is unsuitable for some engines. Consult owners' manual or handbook if in doubt

Approvals, performance and recommendations

Approvals

- GM dexos 1 Gen 2
(License: D10168GJ089)

Performance

- API SN Plus/RC
- Chrysler MS-6395
- Fiat 9.55535-CR-1
- Ford WSS-M2C946-A
- GM 4718M
- GM 6094M
- Honda HTO-06
- ILSAC GF-5

Typical test data		
Test	Test Methods	Results
Viscosity Grade		5W-30
Shelf Life: 60 months from date of filling indicated on the product		
Density, 15 °C, kg/l	ASTM D4052	0.850
Viscosity, Kinematic at 40 °C, mm ² /s	ASTM D445	62.1
Viscosity, Kinematic at 100 °C, mm ² /s	ASTM D445	10.7
Viscosity Index	ASTM D2270	165
Pour Point, °C	ASTM D97	-45
Flash Point COC, °C	ASTM D92	233

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product