



Delo[®] Gear CGA SAE 80W-90

High performance extended drain gear oil

Product description

Delo Gear CGA SAE 80W-90 is a high performance extended drain gear oil, designed for use in heavy-duty automotive vehicle driven axles and differentials.

Delo Gear CGA SAE 80W-90 is formulated with mineral base oils in combination with a high performance additive combination.

Customer benefits

- Designed for extended drain of up to three times longer than standard mineral oils in heavy-duty final drives and differentials
- Formulated for oxidation stability, oil thickening resistance, and helps keep gear cases, bearings and seals free from harmful deposits
- Offers good low-temperature fluidity allowing fast circulation and wear protection during cold start-up
- Extreme pressure (EP) additives promote reliable protection against component scuffing and wear
- Mild-EP non-corrosive additive helps protect sensitive copper alloy components

Product highlights

- **Designed for three-times extended drain**
- **Helps keep gears, bearings deposit-free**
- **Offers low-temperature performance**
- **Promotes scuffing and wear resistance**
- **Formulated for copper alloy protection**

Selected performance standards include:

API	Bosch
MAN	Mercedes-Benz
SAE	Scania
Volvo	ZF

Applications

- Delo Gear CGA SAE 80W-90 is designed for extended drain in heavy duty final drives (driven axles and differentials) in commercial vehicles, and offers service considerably beyond what is normally possible with mineral-based formulations – as much as 3 times longer than standard mineral oils. (The precise service interval varies according to application and service severity – refer to the manufacturers' literature for further details)
- Delo Gear CGA SAE 80W-90 promotes robust performance in high load and high operating temperature conditions. The clean-gear additive system used in the formulation helps prevent sludge and deposit formation.
- Delo Gear CGA SAE 80W-90 has numerous OEM approvals, including MB 235.20 and MAN 342 Type M3 – two particularly demanding norms that few products can meet
- The friction characteristics of Delo Gear CGA SAE 80W-90 make it generally unsuitable for use in synchronised manual transmissions and transaxles, and it should not be used in these applications unless a GL 5 fluid is specifically recommended

Approvals, performance and recommendations

Approvals

- MAN 342 Type M3
- Mercedes-Benz MB-Approval 235.20 *
- Scania STO 1:0 ^[1] *
- Volvo 97321 ^[4]
- ZF TE-ML 05A ^[5]
- ZF TE-ML 12L ^[5]
- ZF TE-ML 12M ^[5]
- ZF TE-ML 16B ^[5]
- ZF TE-ML 17B ^[5]
- ZF TE-ML 19B ^[5]
- ZF TE-ML 21A ^[5]

Performance

- API GL-5
- API MT-1
- Bosch TE-ML 08 ^[2, 3]
- MAN 341 Type GA1 †
- SAE J2360
- ZF TE-ML 07A ^[2]

* Approval is being obtained.

† Approval to be obtained

^[1] Approved for use in gearboxes; also permitted in some lightly-loaded long-haul axle applications (trucks - operation types 0 and 1; busses - operation type 1). Other axle applications require higher viscosity fluids.

^[2] Products meeting the necessary requirements for this specification are approved without listing.

^[3] List formerly administered by ZF.

^[4] Volvo approval number: 97321-018.

^[5] ZF approval number: ZF003513.

Typical test data		
Test	Test Methods	Results
Shelf Life: 48 months from date of filling indicated on the product label		
Density, 15 °C, kg/l	ASTM D1298	0.896
Flash Point COC, °C	ASTM D92	204
Pour Point, °C	ASTM D97	-36
Viscosity, Kinematic, 100°C, mm ² /s	ASTM D445	14.95
Viscosity, Kinematic, 40°C, mm ² /s	ASTM D445	140
Viscosity, Brookfield, -40°C, mPa.s	ASTM D2983	82,000
Viscosity Index	ASTM D2270	108

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product