

Delo Syn-Gear HD SAE 75W-90

High performance synthetic heavy-duty gear oil

Product description

Delo® Syn-Gear HD SAE 75W-90 is a high performance synthetic heavy-duty gear oil suitable for use in heavy duty driven axles and differentials. It is designed with a long-drain capability of 450,000 km and formulated with a combination of synthetic base oils and high performance additives.

Customer benefits

- Extended drain capability of 450,000 km
- High level oxidation stability mitigates against in-service oil thickening, helping to keep gear cases and seals free from deposits
- High Viscosity Index and good low temperature fluidity help contribute to component protection across a wide temperature range
- Effective EP additive technology contributes to critical wear protection under low speed high torque and shock load operations
- Mild EP additive formulation assists in corrosion resistance in vulnerable copper-alloy components
- Up to 3% proven fuel economy improvement compared to conventional gear lubricants when used with Delo Syn-AMT XV SAE 75W-80 in transmissions



Product highlights

- Long-drain capability of 450,000 km
- High performance synthetic technology
- Formulated to protect components across a wide temperature range
- Designed for effective wear and corrosion resistance
- Proven 3% fuel economy when used with Delo Syn-AMT XV SAE 75W-80

Selected specification standards include:

API	Bosch
DAF	Dana Spicer
Iveco	Mack
MAN	Daimler Truck
Meritor	Renault Truck
SAE	Volvo
ZF	

Applications

- Delo Syn-Gear HD SAE 75W-90 is formulated for extended drain in heavy duty final drives (driven axles and differentials) in on- and off-road vehicles. It is suitable for use in severe operating conditions, and in extremely cold or hot environments. The exceptional EP performance allows Delo Syn-Gear HD SAE 75W-90 to be used in many applications where an SAE 140 oil would normally be required
- Low frictional losses in the lubricant film and minimal churning losses due to lower bulk oil viscosity lead to reduced operating temperatures when compared to conventional gear lubricants.
- In addition to its formal OEM approvals, field trial data has been amassed demonstrating its capability for extended drain in numerous other truck applications. Field trial vehicles include those manufactured by MAN, Mercedes and Volvo
- In the USA, this product has been successfully field tested for long drain intervals in class 8 on-highway trucks using axles made Meritor, DAF, Daimler, Dana and MAN.

The friction characteristics of Delo Syn-Gear HD SAE 75W-90 makes it generally unsuitable for use in synchronized manual transmissions and transaxles, and it should not be used in these applications unless a GL 5 fluid is specifically recommended

Approvals, performance and suitable for use

Approvals

- | | |
|---------|---------------------------------------|
| • MAN | 342 Type M2 ^[3] |
| • SAE | J2360 ^[4] |
| • Volvo | Transmission oil 97312 ^[5] |

Performance

- | | |
|-----------|--|
| • API | GL-5 |
| • API | MT-1 |
| • Bosch | TE-ML 08 ^[8] |
| • DAF | Rear axle without hub reduction ^[1] |
| • DAF | Rear axle with hub reduction ^[2] |
| • Mack | GO-J |
| • Meritor | O76-N |
| • ZF | TE-ML 07A ^[7] |

Suitable for use

- | | |
|-----------------|--------------------------------------|
| • Dana Spicer | SHAES 256 Revision A ^[6] |
| • Iveco | Axles |
| • Daimler Truck | DTFR 12B140
(Previously MB 235.8) |
| • Renault Truck | Axles |
| • ZF | TE-ML 05A |
| • ZF | TE-ML 12B |
| • ZF | TE-ML 17B |
| • ZF | TE-ML 19C |
| • ZF | TE-ML 21A |

^[1] May be used with extended changing interval for vehicle/axle combinations where DAF allows this option.

^[2] Including those circumstances where DAF mandates a synthetic oil according to SAE J2360 75W-90.

^[3] MAN approval number: TUC 7880/08.

^[4] Approval number: PRI GL 0871.

^[5] Volvo approval number 020

^[6] This version of the specification is now obsolete

^[7] Products meeting the necessary performance requirements are approved for use by ZF, but there is no product listing.

^[8] List formerly administered by ZF. Products meeting the necessary performance requirements are approved for use, but there is no product listing.

Typical test data		
Test	Test methods	Results
Shelf Life: 60 months from date of filling indicated on the product label.		
Density, 15°C, kg/l	ASTM D1298	0.867
Flash Point COC, °C	ASTM D92	192
Pour Point, °C	ASTM D5950	-45
Viscosity, Kinematic, 100°C, mm²/s	ASTM D445	15.1
Viscosity, Kinematic, 40°C, mm²/s	ASTM D445	108
Viscosity, Brookfield, -40°C, mPa.s	ASTM D2983	137,500
Viscosity Index	ASTM D2270	146

1119

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A Chevron company product