

Delo® TorqForce FD SAE 60

Proven performance heavy-duty final drive oil



Product description

Delo® TorqForce FD SAE 60 is a proven performance heavy-duty final drive oil designed for use in final drives and axles in modern Caterpillar off-road equipment in severe service where fluids meeting the Cat FD-1 specification are recommended.

Customer benefits

- Advanced additive system helps minimise wear in heavily loaded gears and bearings in severe high temperature, high load conditions
- High thermal and oxidation stability helps protect against viscosity increase and deposit formation at drain intervals of up to 4,000 hours
- Designed for rust and corrosion protection in final drive components and rapid circulation at low temperature start-up to help prevent wear
- Foam suppression performance helps maintain reliable component protection and prevent fluid loss

Applications

Delo TorqForce FD SAE 60 is designed specifically for heavy duty final drives and axles in severe service:

- Final drives, axles, differentials and front wheels in Caterpillar equipment where Cat FD-1 performance fluid is specified
- Caterpillar heavy-duty off-highway haul trucks
- Caterpillar wheeled and track-type tractors

Unlike conventional Cat TO-4 type fluids, Delo TorqForce FD SAE 60 is generally not suitable for powershift transmissions or for oil-immersed brakes or clutches, due to different frictional characteristics.

For Caterpillar powershift transmissions, hydraulics and wet brake applications requiring lubricants meeting the Cat TO-4 specification, Chevron recommends the Delo TorqForce series.

Product approvals, performance and recommendations

Performance standards

- Developed independently by Chevron to comply with the requirements of Caterpillar FD-1

Delo[®] TorqForce FD SAE 60

Proven performance heavy-duty final drive oil



Typical Test Data

| DELO TORQFORCE FD SAE 60 | TEST METHOD | RESULT |
|-----------------------------------------------------------------------------------|-------------|--------|
| Typical Shelf Life: 60 months from date of filling indicated on the product label | | |
| Density, 15°C, kg/l | ASTM D4053 | 0.899 |
| Flash Point COC, °C | ASTM D92 | 288 |
| Pour Point, °C | ASTM D5950 | -20 |
| Viscosity, Kinematic, mm ² /s @ 40°C | ASTM D445 | 335 |
| mm ² /s @ 100°C | ASTM D445 | 25.0 |
| Viscosity Index | ASTM D2270 | 97 |

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Delo TorqForce FD SAE 60/AP/PDSV2_03/2024



A Chevron company product

© 2024 Chevron Products Company. Asia-Pacific.
All Rights Reserved.