



HAVOLINE[®] PRO-DS[®] FULL SYNTHETIC MOTOR OIL

SAE 0W-16, 0W-20, 5W-20, 5W-30, 10W-30

PRODUCT DESCRIPTION

Chevron Havoline[®] PRO-DS[®] Full Synthetic Motor Oil is a premium full synthetic oil with Deposit Shield[®] Technology, combined



with a proprietary cleaning booster, designed to provide ultimate protection that prolongs the peak performance and efficiency of your engine, particularly under harsh stop-and-go driving conditions, extreme temperatures and heavy loads. Outstanding protection for vehicles with direct-injection and turbochargers and those that require a full synthetic motor oil. Exceeds the latest and most demanding industry and automaker standards.

FEATURES/BENEFITS

Chevron Havoline PRO-DS Full Synthetic Motor Oils use the latest full synthetic base oils and special cleaning additives including antioxidants and friction modifiers to provide unmatched protection and performance. They are formulated to provide outstanding protection against harmful engine deposits, while providing excellent oxidation protection and volatility control, and superior cold temperature performance over part synthetic and mineral motor oils. Chevron Havoline PRO-DS Full Synthetic Motor Oils are formulated to:

- Provide unsurpassed protection against sludge, varnish and deposit buildup to keep modern engines running cleaner, stronger, and for longer.
- Help maximize the power of your engine while maintaining fuel efficiency and cleanliness.
- Deliver excellent fuel economy retention which helps save on fuel costs.
- Provide excellent protection against aeration to keep oil passages flowing smoothly to protect vital components.

- Deliver superior anti-wear protection for bearings to help preserve engines and turbocharger durability.
- Provide unsurpassed mitigation against Low Speed Pre-Ignition (LSPI) in turbocharged direct injection engines to protect critical engine parts.

PERFORMANCE CLAIMS

- Unparalleled turbocharger cleanliness protection¹.
- Preserves fuel economy up to 50% better than GM's tough dexos1 Gen3 standards².
- Reduces piston deposits.
- Unsurpassed sludge control up to 25% better than GF-6 limits³.
- Meets or exceeds GM's tough dexos1 Gen3 standards (0W-20 and 5W-30).
- Unsurpassed control in fighting temperature-related oil breakdown and oil thickening up to 76% better than GF-6 limits⁴.
- Reduces friction-related wear of critical engine parts up to 25% better than industry GF-6 limits⁵.
- Superior corrosive wear protection of key engine parts up to 64% better than GF-6 limits⁶.

1. Based on GMTC turbocharge test using SAE 5W-30
2. Based on GMVFE fuel economy test using SAE 0W-20
3. Based on Sequence VH sludge and varnish test using SAE 0W-20
4. Based on Sequence IIIH deposit test using SAE 0W-20
5. Based on Sequence IVB valvetrain wear test using SAE 0W-30
6. Based on Sequence VIII corrosion test using SAE 5W-30

Product(s) manufactured in the USA and Colombia.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

15 February 2022
PCMO-90

© 2020-2022 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Havoline, ProDS and Deposit Shield are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS, APPROVALS AND SPECIFICATIONS

Havoline® PRO-DS® Full Synthetic Motor Oils with Deposit Shield® Technology are recommended for advanced, high power density and performance engines with turbochargers, and gasoline direct injection. Recommended for vehicles operating in extreme hot and cold or stop-and-go driving conditions. For use in most domestic and import conventional or hybrid passenger cars, SUVs, pickup trucks and vans, including new and older vehicles.

Meets or exceeds the following industry and OEM standards:

SAE Grade	0W-16	0W-20	5W-20	5W-30	10W-30
API SP/SN Plus/Resource Conserving	X	X	X	X	X
ILSAC GF-6A		X	X	X	X
ILSAC GF-6B	X				
Acura/Honda HTO-06				X	
Chrysler MS-6395		X	X	X	X
Fiat 9.55535-CR-1		X	X	X	X
Ford WSS-M2C960-A1 ¹			X		
Ford WSS-M2C961-A1 ²				X	
Ford WSS-M2C962-A1 ³		X			
GM dexos1 Generation 3		License # D335BACH089		License # D335AACH089	
GM 6094M			X	X	X
GM 4718M				X	X

1 Compatible with Ford WSS-M2C945-A1/B1

2 Compatible with Ford WSS-M2C946-A1/B1

3 Compatible with Ford WSS-M2C947-A1/B1

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

SAE Grade	Test Method	0W-16	0W-20	5W-20	5W-30	10W-30
<i>Product Number</i>		223517	223508	223509	223510	223511
<i>SDS/MSDS Number</i>						
<i>USA</i>		48323	47956	47959	47962	47965
<i>Canada</i>		48325	47957	47960	47963	47966
<i>Mexico</i>		48326	47958	47961	47964	47967
<i>Colombia</i>			44191	44191	44191	44191
Density at 15°C, kg/L	ASTM D4052	0.8447	0.8443	0.8464	0.8479	0.8527
Viscosity, Kinematic mm ² /s at 40°C	ASTM D445	37.3	42.0	43.2	62.0	63.8
mm ² /s at 100°C	ASTM D445	7.2	8.0	8.0	10.8	10.3
Viscosity, Cold Crank (CCS) (cP), CCS @ °C	ASTM D5293	-35/5900	-35/4600	-30/4700	-30/4200	-25/5150
Viscosity Index	ASTM D2270	161	167	161	169	150
Flash Point, °C(°F)	ASTM D92	230(446)	234(453)	227(441)	238(460)	252(486)
Phosphorus, mass%	ASTM D4951	0.077	0.077	0.077	0.077	0.077
Ash, sulphated, mass%	ASTM D874	0.9	0.9	0.9	0.9	0.9
Zinc, mass%	ASTM D4951	0.089	0.089	0.089	0.089	0.089

Minor variations in product typical test data are to be expected in normal manufacturing.

To find the right Chevron Havoline product for your vehicles, please consult www.Havoline.com to find the right motor oil using our Product Selector tool.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.