



HDAX[®] 5200 LOW ASH GAS ENGINE OIL ISOCLEAN[®] CERTIFIED LUBRICANT SAE 15W-40, 30, 40

PRODUCT DESCRIPTION

HDAX[®] 5200 Low Ash Gas Engine ISOCLEAN[®] Certified Lubricants are advanced performance, premium quality, bright stock free, low ash, dispersant/detergent type engine oils. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



- **Clean pistons** — Provides piston cleanliness to help prevent ring sticking and maintain clean, varnish-free piston skirts.
- **Clean crankcases and top decks** — Minimizes the formation of crankcase and valve cover/top deck sludge.
- **Catalyst compatibility** — Formulated to be compatible with exhaust emissions reduction systems.

CUSTOMER BENEFITS

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants deliver value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Low maintenance cost and long engine life**
- **Low wear** — Provide excellent protection against piston, ring, and liner scuffing, scoring, and wear.
- **Valve protection** — The level and type of ash producing additives in the oils provide minimum valve recession with low levels of combustion chamber deposits to minimize the potential for pre-ignition and spark plug fouling.

FEATURES

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants are formulated with premium base oil technology and an additive package containing ashless dispersant, oxidation inhibitors, metallic detergents and a metallic antiwear agent.

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants provide outstanding oxidation and nitration resistance, which minimize the buildup of insolubles and help provide long oil and filter life. HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants give excellent protection against ring and liner scuffing and wear. They also minimize valve recession in four-stroke engines and provide excellent piston and ring belt deposit control and effectively protect against the formation and buildup of engine sludge.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

31 October 2022
GEO-60 ISOCLEAN

© 2018-2022 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, HDAX and ISOCLEAN are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS

HDAX® 5200 Low Ash Gas Engine ISOCLEAN® Certified Lubricants are recommended for four-stroke and selected two-stroke stationary engines fueled by natural gas.

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants are approved for:

- **Caterpillar Energy Solutions GmbH** for CG132, CG170 & CG260 gas engines
- **INNIO Jenbacher** gas engines, as listed in the table below:

Engine Type	Class A	Class B	Class C	Class S	Catalyst
Type 2/3	x			x	x
Type 4A	x			x	x
Type 4BD	x	x	x	x	x
Type 4CE	x	x	x	x	x
Type 6CE	x				x
Type 6FJ	x	x	x	x	x

Where INNIO Jenbacher divides fuel quality into these classes:

- Class A: Clean natural gas that complies with TA 1000-0300.
- Class B: Biogas and Sewage gas.
- Class C: Landfill gas.
- Class S: Special gases requiring special approval like Syngas.
- Catalyst: With an oxidation catalytic converter
- **MAN Diesel & Turbo** engines in operation on natural gas (CNG/LNG) - now MAN Energy Solutions
- **MAN Energy Solutions** for use in MAN ES four-stroke medium speed engines on natural gas (CNG/LNG) - formerly MAN Diesel & Turbo
- All **MWM** gas engines
- **Wärtsilä** gas engines and dual fuel engines with natural gas as main fuel
- All **Waukesha** gas engines burning pipeline quality gas, including 220 GL and Cogeneration

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants are recommended for four-stroke gas-fueled engines manufactured by:

- **Caterpillar**
- **Delaval Enterprise**
- **Dresser-Rand** (Categories I, II, and III)
- **MWM** (DEUTZ)
- **Superior**
- **Worthington**

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants are formulated to meet catalyst compatibility requirements and are especially suited for installations requiring low phosphorus oil to prevent exhaust catalyst poisoning.

HDAX 5200 Low Ash Gas Engine ISOCLEAN Certified Lubricants are suitable for use with fuels containing low levels of sulfur. In sour gas applications, a lubricant with higher base reserve such as HDAX 5300 Medium Ash Gas Engine Oil SAE 40 may be required.

Consult with your Chevron Lubricant Representative or Chevron ISOCLEAN Certified Lubricants Marketer to set specific ISO Cleanliness targets for your business application.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

SAE Grade	15W-40	30	40
<i>Product Number</i>	274317	274318	274319
<i>SDS/MSDS Number</i>	7046	7046	7046
<i>Canada</i>	7046CAN	7046CAN	7046CAN
<i>Mexico</i>	7046MEX	7046MEX	7046MEX
Density at 15°C, kg/L	0.8752	0.8773	0.8790
Viscosity, Kinematic			
cSt at 40°C	126	97.3	124
cSt at 100°C	15.6	11.4	13.5
Viscosity Index	130	104	104
Viscosity, Cold Crank, °C/Poise	-20/61	—	—
Flash Point, °C(°F)	204(399)	215(419)	230(446)
Pour Point, °C(°F)	-30(-22)	-30(-22)	-30(-22)
Sulfated Ash, wt %	0.5	0.5	0.5
Acid Number, ASTM D664	1.0	1.0	1.0
Base Number, ASTM D2896	4.2	4.2	4.2
Phosphorus, ppm	270	270	270
Zinc, ppm	320	320	320

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.