



Delo® 6300 SAE 15W-40

Heavy-Duty Diesel Engine Oil

Product Data Sheet

Customer benefits

- **Wide temperature operation**
SAE 15W-40 multigrade provides good low temperature startability and high temperature protection, allowing use over a wide temperature range.
- **Reduce Maintenance Costs**
Formulated with proven metallic detergent additive system to neutralize harmful acids, helping to prevent corrosion and maintain oil drain interval.
- **Maintain engine life and performance**
Formulated with advanced additives technology and premium base oils to provide good wear protection, deposit control and soot dispersancy performance, helping to protect the engine and running smoothly.

Applications

The following applications whenever the manufacturer recommends SAE 15W-40 multigrade lubricants meeting API CH-4/ SJ performance or below:

- Mixed fleets of diesel engines (high speed, four-stroke, turbocharged or naturally aspirated)
- Commercial road transport
- Off-highway vehicles
- Passenger cars and light duty vehicles
- Agricultural tractors and farm machinery
- High speed diesel engines in marine service (e.g., fishing boat, river transport)

Performance standards

- API CH-4/ SJ

Product features:

Heavy-duty diesel engine oil specifically formulated to meet API CH-4/ SJ. Proven performance designed for use in diesel engines in commercial fleets and off-highway vehicles.

A Chevron company product

All trademarks are property owned by Chevron Intellectual Property LLC.





Typical Key Properties

DELO 6300 SAE 15W-40		
TEST	TEST METHODS	RESULTS
SAE Grade	ASTM	15W-40
Product Code		550051
Base No., mg KOH/g	D 2896	10
Viscosity, mm ² /s @ 100°C	D 445	15.0
Viscosity, mm ² /s @ 40°C	D 445	114.8
Viscosity Index	D 2270	136
Pour Point, °C	D97	-35

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com