

Delo[®] 6300 SAE 15W-40

Heavy-Duty Diesel Engine Oil



Product description

Heavy-duty diesel engine oil specifically formulated to meet API CH-4/ SJ. Proven performance designed for use in diesel engines in commercial fleets and off-highway vehicles.

Customer benefits

- **Wide temperature operation**
SAE 15W-40 multigrade provides good low temperature startability and high temperature protection, allowing use over a wide temperature range.
- **Reduce maintenance costs**
Formulated with proven metallic detergent additive system to neutralize harmful acids, helping to prevent corrosion and maintain oil drain interval.
- **Maintain engine life and performance**
Formulated with advanced additives technology and premium base oils to provide good wear protection, deposit control and soot dispersancy performance, helping to protect the engine and running smoothly.

Delo[®] 6300 SAE 15W-40

Heavy-Duty Diesel Engine Oil



Applications

The following applications whenever the manufacturer recommends SAE 15W-40 multigrade lubricants meeting API CH-4/ SJ performance or below:

- Mixed fleets of diesel engines (high speed, four-stroke, turbocharged or naturally aspirated)
- Commercial road transport
- Off-highway vehicles
- Passenger cars and light duty vehicles
- Agricultural tractors and farm machinery
- High speed diesel engines in marine service (e.g., fishing boat, river transport)

Product approvals, performance and recommendations

Performance

- API CH-4/SJ

Delo[®] 6300 SAE 15W-40

Heavy-Duty Diesel Engine Oil



Typical test data

DELO [®] 6300 SAE 15W-40	TEST METHODS	RESULTS
SAE Grade		15W-40
Product Code		550051
Base No., mg KOH/g	ASTM D2896	10
Viscosity,		
mm ² /s @ 40°C	ASTM D445	114.8
mm ² /s @ 100°C	ASTM D445	15.0
Viscosity Index	ASTM D2270	136
Pour Point, °C	ASTM D97	-35

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Delo[®] 6300 SAE 15W-40/MEA/CHV/PDSv1_18/12/2018



Chevron company product

© 2025 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.