



Delo[®] 400 SAE 30

Proven performance engine oil

Product description

Delo 400 SAE 30 is a proven performance mixed fleet engine oil designed for use in older four-stroke gasoline and diesel engines. Delo 400 SAE 30 is formulated with premium base oils, robust dispersancy and detergency additives with oxidation, wear, corrosion and foam inhibitors.

Customer benefits

- Offers good oxidation stability and deposit control, helping keep engines clean and reliable
- Designed to minimise engine wear and maintenance intervals
- Formulated to minimise oil consumption, controlling costs
- High detergency provides good piston ring deposit and sludge control

Product highlights

- **Offers good oxidation stability**
- **Designed to minimise wear**
- **Helps improve oil consumption**
- **Provides good deposit and sludge control**

Selected specification standards include:

API	Daimler
MAN	MTU

Applications

- Delo 400 SAE 30 is a mixed fleet engine oil recommended for older four-stroke gasoline and diesel engines that require a monograde engine oil. It is formulated for use in older engines running on normal, high and low sulphur diesel fuels. Delo 400 SAE 30 is not recommended for use in DDC two-stroke engines.

Performance

- API SJ/CF
- Daimler MB 228.2
- MAN M3275-1, 270
- MTU Category 1

Approvals, performance and recommendations

Approvals

- MTU Category 2
- Delo 400 SAE 30 is approved for use in MTU engines including Series 8000

Delo 400 SAE 30 is not suitable for Series 4000-03 M73-M93L IMO III, 4000-04 C/R/T, 4000-05 G/C/T, 4000-05 IMO III, 2000M41A IMO III, 956 TB31/32/33/34, 1163 TB32 Genset, S 60 and 1600) and DDC engine Series 2000/4000

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 30
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.882
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	94
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	11.5
Viscosity Index	ASTM D2270	110
Pour point, °C	ASTM D97	-27
Flash point COC, °C	ASTM D92	236
Total Base Number, mg KOH/g	ASTM D2896	10.1
Sulphated Ash, %wt	ASTM D874	1.5

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product