



# CHEVRON SUPREME MOTOR OIL ISOCLEAN® CERTIFIED LUBRICANT SAE 10W-30

---

## PRODUCT DESCRIPTION

Chevron Supreme ISOCLEAN® Certified Lubricant SAE 10W-30 is a premium automotive motor oil that protects against deposit and sludge formation and provides excellent wear protection to critical engine parts. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



## CUSTOMER BENEFITS

Chevron Supreme ISOCLEAN Certified Lubricant SAE 10W-30 delivers value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Excellent antiwear protection**
- **Protection against thermal breakdown**
- **Clean engines** and positive crankcase ventilation systems resulting in minimal deposits under heavy load and stop-and-go driving conditions.
- **Meets or exceeds warranty requirements** of car and light truck manufacturers relying on an API SN, SM, SL or SJ service category motor oil.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

© 2017 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark and ISOCLEAN are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

- **Energy Savings** — API Resource Conserving designation

## FEATURES

Chevron Supreme ISOCLEAN Certified Lubricant SAE 10W-30 is a premium quality automotive engine oil.

It is formulated with high quality base stocks, and robust additive packages including shear-stable viscosity index improvers, detergents, dispersants, anti-wear agents, corrosion inhibitors, antioxidants and foam inhibitors.

Their anti-wear additives provide excellent wear protection of critical engine parts.

A high level of dispersancy in Chevron Supreme ISOCLEAN Certified Lubricant SAE 10W-30 protects against deposit and sludge formation in stop-and-go driving, sustained high temperature operation, and protects against corrosion.

Its excellent high temperature oxidation stability helps prevent viscosity increase and oil gelling in the crankcase. They help keep PCV systems clean to maintain smooth engine performance.

21 August 2017  
PCMO-20 ISOCLEAN

## APPLICATIONS

Chevron Supreme ISOCLEAN® Certified Lubricant SAE 10W-30 is suitable for use in four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. It is excellent for high-revving engines in small cars and light trucks. It is suitable for use in turbocharged engines. Chevron Supreme ISOCLEAN Certified Lubricant SAE 10W-30 may also be suitable for use in natural gas engines in small cars and light trucks after consulting with the appropriate original equipment manufacturer's lubrication recommendations.

It is suitable for use in many older vehicles and a few late model cars and trucks, often those with larger 6-cylinder and V-8 and/or high performance engines. SAE 10W-30 is also designated as a Resource Conserving lubricant by API.

Note: Always consult your owner's manual regarding viscosity grade for your application.

Chevron Supreme ISOCLEAN Certified Lubricant SAE 10W-30 meets:

- **API Service Categories**
  - SN
  - SM, SL, SJ and all previous API "S" categories
  - Resource Conserving for API SN
  - ILSAC GF-5
- **manufacturers' performance requirements**
  - **FCA US LLC** (formerly known as Chrysler Group LLC) MS-6395
  - **General Motors**  
GM 6094M

Consult with your Chevron Lubricant Representative or Chevron ISOCLEAN Certified Lubricants Marketer to set specific ISO Cleanliness targets for your business application.

## TYPICAL TEST DATA

SAE Grade	10W-30
Product Number	274315
SDS Number	17483
Canada	17483CAN
Mexico	17483MEX
API Gravity	30.5
Viscosity, Kinematic	
cSt at 40°C	68.4
cSt at 100°C	10.3
Viscosity, Cold Crank, °C/Poise	-25/62
Viscosity Index	137
Flash Point, °C(°F)	> 200(392)
Pour Point, °C(°F)	-36(-33)
Sulfated Ash, wt %	0.9
Base Number, ASTM D2896	8.4
Phosphorus, wt %	0.076
Zinc, wt %	0.085

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.