



Havoline® Easy Cool 40/60

Product Data Sheet

Customer benefits

Havoline Easy Cool 40/60 ready mixed contains mono ethylene glycol and helps to prevent winter freezing and summer overheating. It comes ready for use.

- Provides protection against corrosion
- Protects all metals including aluminium
- Prevents scale build up
- Compatible with conventional (green) antifreeze

Applications

- Havoline Easy Cool 40/60 ready mixed is recommended for use in applications requiring ASTM D3306 performance standard.
- Naturally aspirated and turbocharged gasoline engines in passenger cars.
- Light duty truck diesel engines.
- Havoline Easy Cool 40/60 ready mixed should not be mixed with other engine coolants. Most coolant blends are based on carefully balanced mixtures of various corrosion inhibitors. Mixing of coolants with different inhibitor packages can lead to loss of corrosion protection.

Performance Standards

Havoline Easy Cool 40/60 meets:

- ASTM D3306

Product features:

Havoline Easy Cool 40/60 is a carboxylate corrosion inhibitor and mono ethylene glycol based antifreeze coolant for automotive gasoline engine and light duty diesel engine applications. Havoline Easy Cool 40/60 is prediluted and contains inhibitors providing effective protection against freezing, boiling, rust and corrosion when used as recommended. There is no need to add water.

A **Chevron** company product

All trademarks are property owned by Chevron Intellectual Property LLC.





Typical properties

HAVOLINE EASY COOL 40/60 TEST	RESULTS
Product Code	510575
Appearance	Green
pH, ASTM D1287	8.5
Density @ 20 °C	1.054
Reserve Alkalinity (pH 5.5) ASTM D1121	0.93
Freezing Point, °C, ASTM D1177	-22
Silicate, %*	None

* As anhydrous alkali metasilicate

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Global Lubricants, Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com