

Havoline SuperMatic 4T

High Performance Premium Four-Stroke Motorcycle Oil



Product description

A mineral oil with **Havoline® C.O.R.E.+ Technology** that lubricates, protects, and cleans as you ride.

Customer benefits and product features

Customer benefits

- **Tailored scooter additive package**
Formulated with a scooter-unique additive package, this oil ensures reliable oxidation protection, detergency, and low frictional properties.
- **Smooth and clean engine performance**
With a thermal stable oil, it protects and keeps your engine clean and running smoothly.
- **Better protection against viscosity increase**
Offers protection against viscosity increase, ensuring oil flows smoothly and effectively controls heat degradation of the oil.

Product features

- **Havoline C.O.R.E.+ Technology** delivers four key benefits:
 - Cleans and protects – maintains efficient engine performance.
 - Oxidation stability – protects against oil degradation.
 - Reduces engine heat damage – delivers continuous and superior oil stability.
 - Enhances fuel economy – improves efficiency for a smoother ride.
- Havoline scooter oils ensure your scooter always performs at its best.

Havoline SuperMatic 4T

High Performance Premium Four-Stroke Motorcycle Oil



Applications

- Air- and liquid-cooled four-stroke scooter engines
- Suitable for scooter engines that require better protection against wear (SAE 20W-40)
- Scooters with exhaust catalytic converters
- Not recommended for use in scooters where a multi-grade JASO MA engine oil is specified
- Not recommended for use in motorcycles with oil-immersed clutches or with combined engine, clutch and gearbox lubrication from a single sump
- SAE 10W-40 viscosity grade is recommended by Yamaha

Product approvals, performance and recommendations

Performance

- T903:2016 JASO MB
JASO Identification Number: M065CVX117 (SAE 10W-40)
M065CVX125 (SAE 20W-40)
- Meets the specifications of API SN

Havoline SuperMatic 4T

High Performance Premium Four-Stroke Motorcycle Oil



Typical test data

HAVOLINE SUPERMATIC 4T	RESULTS	
SAE Grade	10W-40	20W-40
Product Code	500710	500718
Base No., D2896, mg KOH/g	7.7	7.8
Pour Point, oC	-39	-39
Sulfated Ash, m %	1.0	0.8
Viscosity, mm ² /s @ 100°C	13.8	14.5
Phosphorus, m%	0.08	0.08

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center

[Visit Product Information Center >](#)

Havoline SuperMatic 4T/Asia Pacific/CHV/PDSv1_04/2024



A Chevron company product

© 2024 Chevron Products Company. Asia Pacific.
All Rights Reserved.