



Havoline® Fully Synthetic SAE 5W-40

Passenger Car Motor Oil

Product Data Sheet

Customer benefits

Preserves and protects engines

Proven metallo-organic anti-wear additive system protects engines under all operating conditions by providing excellent wear control in even the most sophisticated valve train mechanisms, including those with variable valve timing. Low viscosity, multigrade, formulation provides additional protection reduces internal engine friction. Enhanced corrosion protection ensures compatibility with gasoline/ethanol blended fuels up to and including E85.

Maintains high power and performance

Works immediately upon contact with an engine's moving parts to create a protective coating that shields the engine against the deposits that lead to loss of performance. Provides excellent control of piston and ring deposits under high temperature conditions. Special friction modifiers assist in reducing internal engine friction for maximum fuel economy.

Saves on maintenance costs

High thermal stability and excellent oxidation resistance provides outstanding protection against in-service oil degradation that contributes to filter blocking and sludge formation in the oil galleries, crankcase and valve train.

Reduces fuel consumption

Specifically tailored viscosity characteristics and effective friction modifier minimize internal engine frictional losses.

Lower oil consumption

Low volatility, hydro-cracked base oil minimizes oil loss through evaporation.

Applications

- Specially designed for high performance gasoline and diesel engines in passenger cars, in particular those of European designs.
- Suitable for use in naturally aspirated and turbocharged diesel in passenger cars and light trucks where ACEA A3/B4 is required.
- Naturally aspirated, turbocharged gasoline engines in passenger cars where API SN or earlier API "S" performance categories are specified.
- Light truck gasoline engines where API SN or earlier API "S" performance categories are specified.

Product features

- **Havoline® Formula** is a high performance, multigrade motor oil formulated for use in passenger car and light truck gasoline and diesel engines under a wide range of operating conditions.
- **Havoline® Formula** is formulated with **Deposit Shield™** to provide outstanding protection and value for cleaner, smoother-running engines.
- **Havoline® with Deposit Shield™** is an advanced detergent formula that helps prevent deposit build up for improved oil stability and increased engine durability.
- **Havoline® with Deposit Shield™** provides superior viscosity control that helps maintain engine power and reduces maintenance costs.

A **Chevron** company product





continued

Performance standards

- VW 502 00 / 505 00 (Approved)
- RN 0700 / 0710 (Approved)

Meets the requirements of :

- ACEA A3/B4
- API SN
- Daimler MB 229.3
- Porsche A40
- PSA Peugeot Citroen B71 2296



continued

Typical test data

HAVOLINE® FULLY SYNTHETIC	RESULTS
SAE Grade	5W-40
Product Code	502900
Base No. D2896, mg KOH/g	10.8
Phosphorus, m %	0.11
Sulfated Ash, m %	1.4
Viscosity, mm ² /s @ 100°C	14.4
Viscosity Index	172
Zinc, m%	0.122

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com

A Chevron company product
All trademarks are property owned by Chevron Intellectual Property LLC.

HAVOLINE-FULLY-SYNTHETIC-SAE-5W-40/MEA/PDSv1_03/11/2022
© 2022 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.