Havoline[®] ProDS Fully Synthetic ECO SAE 5W-40



Passenger Car Motor Oil

Product description

Havoline[®] **ProDS Fully Synthetic ECO SAE 5W-40** is premium fully synthetic motor oil with Deposit Shield Technology, a cleaning booster, designed to provide advanced protection that helps prolong the peak performance and efficiency of high performance engines, particularly under harsh stop-and-go driving conditions and heavy loads.

It is formulated to offer outstanding protection for vehicles with direct-injection and turbochargers and those that require a full synthetic motor oil.

Customer benefits and product features

Customer benefits

- Engineered to help provide outstanding mitigation against Low Speed Pre-Ignition (LSPI) in turbocharged gasoline direct injection (GDI) engines to protect critical engine parts
- Formulated to offer advanced protection against sludge, varnish and piston deposit build-up to help keep modern engines running cleaner and longer
- Offers outstanding protection against wear and corrosion to help preserve engines and turbocharger durability
- Designed for exceptional turbocharger cleanliness protection
- Offers excellent degradation control for long automaker oil change intervals

Product features

 Havoline ProDS Fully Synthetic ECO SAE 5W-40 with Deposit Shield Technology uses fully synthetic base oils and advanced additives technologies including special antioxidants and friction modifiers to hep provide outstanding protection and performance. It exhibits outstanding protection against heat, pressure, corrosion, and wear while providing excellent oxidation protection and volatility control. Havoline[®] ProDS Fully Synthetic ECO SAE 5W-40



Passenger Car Motor Oil

Applications

Havoline ProDS Fully Synthetic ECO SAE 5W-40 with Deposit Shield Technology is recommended by Chevron for use in:

- Advanced, high power density and performance engines with turbochargers, gasoline direct injection
- Vehicles operating in extremely hot, or stop-and-go driving conditions
- Passenger cars, pickup trucks, SUVs and working vans in new and older vehicles
- Acura, Chrysler, FCA, Ford, GM, Honda, Mazda, Nissan and Toyota engines where an API SQ SAE 5W-40 lubricant is recommended

Approvals, performance and recommendations

Developed independently by Chevron to comply with the following performance standards and specifications:

HAVOLINE [®] PRODS FULLY SYNTHETIC ECO	SAE 5W-40
API SQ	Approved

Consult OEM representatives for independent verification, updates and recommendations.

Havoline[®] ProDS Fully Synthetic ECO SAE 5W-40

Passenger Car Motor Oil

HAVOLINE[®] PRODS FULLY SYNTHETIC ECO

Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and

This Product Data Sheet (PDS) was produced for the Asia-Pacific region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

SAE Grade		5W-40
Product Code		500064
Density at 15°C kg/l	ASTM D4052	0.85
Kinematic Viscosity,		
mm²/s @ 40°C	ASTM D445	61.6
mm²/s @ 100°C	ASTM D445	14.2
Viscosity Index	ASTM D2270	171
Pour Point, °C	ASTM D5950	-39
Phosphorous mass %	ASTM D4951	0.07
Sulfated Ash, mass %	ASTM D874	0.72
Zinc, mass %	ASTM D4951	0.08

Typical test data

Visit Product Information Center > Havoline® ProDS FS ECO SAE 5W-40/Asia Pacific/CHV/PDSv1_04/2025



0425

