

Delo[®] 400 NG SAE 15W-40

Heavy Duty Mobile Gas Engine Oil



Product description

Delo[®] 400 NG SAE 15W-40 with ISOSYN[®] Technology is a premium medium ash CNG/ LNG engine oil formulated to deliver outstanding protection and long drain performance in a wide variety of medium and heavy duty Natural Gas fuelled applications.

Customer benefits and product features

Customer benefits

Alternative fuel performance

Formulated especially for medium and heavy-duty vehicles powered by Natural Gas (CNG/ LNG) fuelled engines.

Low wear

Helps provides excellent protection against piston, ring, and liner scuffing, scoring, and wear, including wear protection for slider follower valve trains in alternative fuel engines.

Clean crankcases and top decks

Helps minimise the formation of sludge in the crankcase and in the valve rocker cover/top deck area.

Helps prevents corrosion

Excellent oxidation and nitration resistance help prevent bearing corrosion.

Excellent piston and ring belt deposit control

An optimized blend of detergents, dispersants, and inhibitors help provide excellent deposit control throughout the entire engine.

Product features

Delo[®] 400 NG SAE 15W-40 has demonstrated excellent field performance and the capability to help customers minimize operating costs in a variety of operations including city bus service, delivery and refuse truck service, long- distance truck service.

Delo[®] 400 NG SAE 15W-40

Heavy Duty Mobile Gas Engine Oil



Applications

- Natural Gas (CNG/LNG) fuelled urban buses
- Natural Gas fuelled delivery and refuse trucks
- Natural Gas fuelled long-distance trucks

Product approvals, performance and recommendations

Performance standards

- Cummins CES 20085 (Letter of Conformance)
- Detroit Diesel DDC93K216 (Letter of Conformance)

Delo[®] 400 NG SAE 15W-40

Heavy Duty Mobile Gas Engine Oil



Typical test data

| DELO [®] 400 NG SAE 15W-40 | RESULT |
|--|---------------|
| SAE Grade | 15W-40 |
| Product Code | 500288 |
| Base No., | |
| ASTM D2896, mg KOH/g | 6.1 |
| ASTM D4739, mg KOH/g | 5.1 |
| Pour Point, | |
| ASTM D97, °C | -27 |
| Viscosity, Kinematic, | |
| ASTM D 445, mm ² /s @ 40°C | 121 |
| ASTM D 445, mm ² /s @ 100°C | 15.7 |
| Viscosity Index, ASTM D 2270 | 133 |

1812

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

Visit Product Information Center >

DELO400NG15W-40/AP/PDSv2_26/12/2018



A Chevron company product

© 2023 Chevron Products Company. Asia-Pacific.

All Rights Reserved.